

Web2c

for version 2022
January 2022

Karl Berry
Olaf Weber
<https://tug.org/web2c>

This file documents the installation and use of the programs in Web2c, an implementation of Donald Knuth's TeX system.

Copyright © 1996, 1997, 1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2007, 2008, 2009, 2010-2022 Karl Berry & Olaf Weber.

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this manual under the conditions for verbatim copying, provided that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

Permission is granted to copy and distribute translations of this manual into another language, under the above conditions for modified versions, except that this permission notice may be stated in a translation

Table of Contents

1	Introduction	1
2	Installation	3
2.1	configure options	3
2.2	Compile-time options	4
2.3	Additional targets	5
2.4	Trip, trap, and mptrap: Torture tests	5
3	Commonalities	7
3.1	Option conventions	7
3.2	Common options	7
3.3	Path searching	9
3.4	Output file location	9
4	Three programs: Metafont, MetaPost, and T_EX	11
4.1	Runtime options	11
4.2	Initial and virgin	12
4.3	Memory dumps	12
4.3.1	Creating memory dumps	12
4.3.2	Determining the memory dump to use	13
4.3.3	Hardware and memory dumps	13
4.4	Editor invocation	14
4.5	\input filenames	14
4.5.1	\input quoted filename: \input "some name"	15
4.5.2	\input braced filename: \input{some name}	15
4.5.3	\input filename caveats	15
5	T_EX: Typesetting	17
5.1	tex invocation	17
5.2	Initial T _E X	19
5.3	Formats	20
5.4	Languages and hyphenation	21
5.4.1	MLT _E X: Multi-lingual T _E X	21
5.4.1.1	\charsubdef: Character substitutions	21
5.4.1.2	\tracingcharsubdef: Substitution diagnostics	22
5.4.2	TCX files: Character translations	22
5.4.3	Patgen: Creating hyphenation patterns	24
5.5	Shell escapes	24
5.6	IPC and T _E X	25
5.7	Extended T _E X engines	25

6	Metafont: Creating typeface families	27
6.1	mf invocation	27
6.2	Initial Metafont	28
6.3	Modes: Device definitions for Metafont	29
6.4	Online Metafont graphics	30
6.5	GFtoDVI: Character proofs of fonts	31
6.6	MFT: Prettyprinting Metafont source	32
7	MetaPost: Generating PostScript	34
7.1	mpost invocation	34
7.2	Initial MetaPost	36
7.3	DVItoMP: DVI to MPX conversion	36
8	BibT_EX: Bibliographies	37
8.1	BibT _E X invocation	37
8.2	Basic BibT _E X style files	38
9	WEB: Literate programming	39
9.1	Tangle: Translate WEB to Pascal	39
9.2	Weave: Translate WEB to T _E X	40
9.3	Pooltype: Display WEB pool files	40
10	DVI utilities	42
10.1	DVIcopy: Canonicalize virtual font references	42
10.2	DVItype: Plain text transliteration of DVI files	42
10.2.1	DVItype output example	43
11	Font utilities	46
11.1	Font file formats	46
11.2	GFtoPK: Generic to packed font conversion	47
11.3	PKtoGF: Packed to generic font conversion	47
11.4	PKtype: Plain text transliteration of packed fonts	47
11.5	GFtype: Plain text transliteration of generic fonts	49
11.6	TFtoPL: T _E X font metric to property list conversion	51
11.7	PLtoTF: Property list to T _E X font metric conversion	53
11.8	VFtoVP: Virtual font to virtual property lists	53
11.9	VPtoVF: Virtual property lists to virtual font	54
11.10	Font utilities available elsewhere	54
Appendix A	Legalisms	55
Appendix B	References	56
Index	58

1 Introduction

This manual corresponds to version 2022 of Web2c, released in January 2022.

Web2c (also spelled Web2C) is the name of a T_EX implementation, originally for Unix, but now also running under Windows and other operating systems. By *T_EX implementation*, we mean all of the standard programs developed by the Stanford T_EX project led by Donald E. Knuth: Metafont, DVItyp_e, GFtoDVI, BibT_EX, Tangle, etc., as well as T_EX itself. Other programs are also included: DVicopy, written by Peter Breitenlohner, MetaPost and its utilities (derived from Metafont), by John Hobby, and many more.

General strategy: Web2c works, as its name implies, by translating the WEB source in which T_EX is written into C source code. Its output is not self-contained, however; it makes extensive use of many macros and functions in a library (the `web2c/lib` directory in the sources). Therefore, it will not work without change on an arbitrary WEB program.

Availability: All of Web2c is freely available—“free” both in the sense of no cost (free ice cream) and of having the source code to modify and/or redistribute (free speech). See Section “unixtex.ftp” in *Kpathsea*, for the practical details of how to obtain Web2c.

Different parts of the Web2c distribution have different licensing terms, however, reflecting the different circumstances of their creation; consult each source file for exact details. The main practical implication for redistributors of Web2c is that most of the executables are covered by the GNU General Public License or GNU Lesser General Public License, and therefore anyone who gets a binary distribution must also be able to get the sources, as explained by the terms of the GPL (<https://gnu.org/licenses/>). The GPL covers the Web2c executables, including `tex`, because the Free Software Foundation sponsored the initial development of the *Kpathsea* library that Web2c uses. The basic source files from Stanford, however, have their own copyright terms or are in the public domain, and are not covered by the GPL.

History: Tomas Rokicki originated the T_EX-to-C system in 1987, working from the first change files for T_EX under Unix, which were done primarily by Howard Trickey and Pavel Curtis. Tim Morgan then took over development and maintenance for a number of years; the name changed to Web-to-C somewhere in there. In 1990, Karl Berry became the maintainer. He made many changes to the original sources, and started using the shorter name Web2c. In 1997, Olaf Weber took over, and then in 2006, Karl started taking care of it again. No significant development or changes have been needed for many years, though dozens of other people have contributed in many ways; their names are listed in the `ChangeLog` files.

Originally, Web2c was distributed as its own package, alongside the original web programs from Stanford and other components. It was also the basis for the teT_EX distribution (now discontinued). Around 2004, the packaging focus shifted entirely to the T_EX Live distribution (<https://tug.org/texlive/>), though the same Web2c is at the heart of the release.

Other acknowledgements by Karl: The University of Massachusetts at Boston (particularly Rick Martin and Bob Morris) provided computers and ftp access to me for many years. Richard Stallman at the Free Software Foundation employed me while I wrote the original path searching library (for the GNU font utilities). (rms also gave us Emacs, GDB, and GCC, without which I cannot imagine developing Web2c.) And, of course, T_EX would not exist in the first place without Donald E. Knuth.

Further reading: See Appendix B [References], page 56.

2 Installation

(A copy of this chapter is in the distribution file `web2c/INSTALL`.)

Installing Web2c is mostly the same as installing any other Kpathsea-using program. Therefore, for the basic steps involved, see Section “Installation” in *Kpathsea*. (A copy is in the file `kpathsea/INSTALL`.)

One peculiarity to Web2c is that the source distribution comes in two files: `web.tar.gz` and `web2c.tar.gz`. You must retrieve and unpack them both. (We have two because the former archive contains the very large and seldom-changing original WEB source files.) See Section “unixtex.ftp” in *Kpathsea*.

Another peculiarity is the MetaPost program. Although it has been installed previously as `mp`, as of Web2c 7.0 the installed name is now `mpost`, to avoid conflict with the `mp` program that does prettyprinting. This approach was recommended by the MetaPost author, John Hobby. If you as the \TeX administrator wish to make it available under its shorter name as well, you will have to set up a link or some such yourself. And of course individual users can do the same.

For solutions to common installation problems and information on how to report a bug, see the file `kpathsea/BUGS` (see Section “Bugs” in *Kpathsea*). See also the Web2c home page, <http://www.tug.org/web2c>.

Points worth repeating:

- Before starting the standard compilation and installation you must install the basic fonts, macros, and other library files. See Section “Installation” in *Kpathsea*.
- If you do not wish to use the standard file locations, see Section “Changing search paths” in *Kpathsea*.
- Some Web2c features are enabled or disabled at `configure` time, as described in the first section below.

2.1 configure options

This section gives pointers to descriptions of the ‘`--with`’ and ‘`--enable`’ `configure` arguments that Web2c accepts. Some are specific to Web2c, others are generic to all Kpathsea-using programs.

For a list of all the options `configure` accepts, run ‘`configure --help`’. The generic options are listed first, and the package-specific options come last.

For a description of the generic options (which mainly allow you to specify installation directories) and basic `configure` usage, see Section “Running `configure` scripts” in *Autoconf*, a copy is in the file `kpathsea/CONFIGURE`.

‘`--disable-dump-share`’

Do not make `fmt/base/mem` files sharable across different endian architectures. See Section 4.3.3 [Hardware and memory dumps], page 13.

```

'--without-maketexmf-default'
'--without-maketexpk-default'
'--without-maketextfm-default'
'--with-maketextex-default'
    Enable or disable the dynamic generation programs. See Section “mktex con-
    figuration” in Kpathsea. The defaults are the inverse of the options, i.e., every-
    thing is enabled except mktextex.

'--enable-shared'
    Build Kpathsea as a shared library. See Section “Shared library” in Kpathsea.

'--with-editor=cmd'
    Change the default editor invoked by the ‘e’ interactive command. See
    Section 4.4 [Editor invocation], page 14.

'--with-epsfwin'
'--with-hp2627win'
'--with-mftalkwin'
'--with-nextwin'
'--with-regiswin'
'--with-suntoolswin'
'--with-tektronixwin'
'--with-unitermwin'
'--with-x'
'--with-x-toolkit=KIT'
'--with-x11win'
'--with-x11'
    Define Metafont graphics support; by default, no graphics support is enabled.
    See Section 6.4 [Online Metafont graphics], page 30.

'--x-includes=dir'
'--x-libraries=dir'
    Define the locations of the X11 include files and libraries; by default, configure
    does its best to guess). See Section “Optional Features” in Autoconf. A copy
    is in kpathsea/CONFIGURE.

```

2.2 Compile-time options

In addition to the `configure` options listed in the previous section, there are a few things that can be affected at compile-time with C definitions, rather than with `configure`. Using any of these is unusual.

To specify extra compiler flags (‘-Dname’ in this case), the simplest thing to do is:

```
make XCFLAGS="ccoptions"
```

You can also set the `CFLAGS` environment variable before running `configure`. See Section “configure environment” in *Kpathsea*.

Anyway, here are the possibilities:

`'-DFIXPT'`

`'-DNO_MF_ASM'`

Use the original WEB fixed-point routines for Metafont and MetaPost arithmetic calculations regarding fractions. By default, assembly-language routines are used on x86 hardware with GNU C (unless `'NO_MF_ASM'` is defined), and floating-point routines are used otherwise.

`'-DIPC_DEBUG'`

Report on various interprocess communication activities. See Section 5.6 [IPC and T_EX], page 25.

2.3 Additional targets

Web2c has several Make targets besides the standard ones. You can invoke these either in the top level directory of the source distribution (the one containing `kpathsea/` and `web2c/`), or in the `web2c/` directory.

`'c-sources'`

Make only the C files, translated from the Web sources, presumably because you want to take them to a non-Unix machine.

`'formats'`

`'install-formats'`

Make or install all the memory dumps (see Section 4.3 [Memory dumps], page 12). By default, the standard plain formats plus `latex.fmt` are made. You can add other formats by redefining the `fmts`, `bases`, and `mems` variables. See the top of `web2c/Makefile` for the possibilities.

`'fmts'`

`'install-fmts'`

Make or install the T_EX `.fmt` files. See Section 5.2 [Initial TeX], page 19.

`'bases'`

`'install-bases'`

Make or install the Metafont `.base` files. See Section 6.2 [Initial Metafont], page 28.

`'mems'`

`'install-mems'`

Make or install the MetaPost `.mem` files. See Section 7.2 [Initial MetaPost], page 36.

`'triptrap'`

`'trip'`

`'trap'`

`'mptrap'` To run the torture tests for T_EX, Metafont, and MetaPost (respectively). See the next section.

2.4 Trip, trap, and mptrap: Torture tests

To validate your T_EX, Metafont, and MetaPost executables, run `'make triptrap'`. This runs the `trip`, `trap`, and `mptrap` “torture tests”. See the files `triptrap/tripman.tex`,

`triptrap/trapman.tex`, and `triptrap/mptrap.readme` for detailed information and background on the tests.

The differences between your executables' behavior and the standard values will show up on your terminal. The usual differences (these are all acceptable) are:

- string usage and table sizes;
- glue set ratios;
- 'down4', 'right4', and 'y4' commands in DVItypex output;
- dates and times.

Any other differences are trouble. The most common culprit in the past has been compiler bugs, especially when optimizing. See Section "TeX or Metafont failing" in *Kpathsea*.

The files `trip.diffs`, `mftrap.diffs`, and `mptrap.diffs` in the `triptrap` directory show the standard diffs against the original output. If you diff your diffs against these files, you should come up clean. For example

```
make trip >&mytrip.diffs
diff triptrap/trip.diffs mytrip.diffs
```

To run the tests separately, use the targets `trip`, `trap`, and `mptrap`.

To run simple tests for all the programs as well as the torture tests, run 'make check'. You can compare the output to the distributed file `tests/check.log` if you like.

3 Commonalities

Many aspects of the T_EX system are the same among more than one program, so we describe those pieces together, here.

Another kind of commonality is the extensions to T_EX that are available across all the engines; see Section 5.7 [TeX extensions], page 25.

3.1 Option conventions

To provide a clean and consistent behavior, we chose to have all these programs use the GNU function `getopt_long_only` to parse command lines. However, we do use in a restricted mode, where all the options have to come before the rest of the arguments.

As a result, you can:

- use ‘-’ or ‘--’ to start an option name;
- use any unambiguous abbreviation for an option name;
- separate option names and values with either ‘=’ or one or more spaces;
- use filenames that would otherwise look like options by putting them after an option ‘--’.

By convention, non-option arguments, if specified, generally define the name of an input file, as documented for each program.

If a particular option with a value is given more than once, it is the last value that counts.

For example, the following command line specifies the options ‘foo’, ‘bar’, and ‘verbose’; gives the value ‘baz’ to the ‘abc’ option, and the value ‘xyz’ to the ‘quux’ option; and specifies the filename `-myfile-`.

```
-foo --bar -verb -abc=baz -quux karl --quux xyz -- -myfile-
```

3.2 Common options

All of these programs accept the standard GNU ‘--help’ and ‘--version’ options, and several programs accept ‘--verbose’. Rather than writing identical descriptions for every program, they are described here.

‘--help’ Print a usage message listing basic usage and all available options to standard output, then exit successfully.

‘--verbose’
 Print progress reports to standard output.

‘--version’
 Print the version number to standard output, then exit successfully.

T_EX, Metafont, and MetaPost have a number of additional options in common:

‘-cnf-line=str’
 Parse *str* as if it were a line in the `texmf.cnf` configuration file, overriding all other settings. See Section “Path searching options” in *Kpathsea*.

`'-file-line-error'`

`'-no-file-line-error'`

Change (or do not change) the way error messages are printed. The alternate style looks like error messages from many compilers and is easier to parse for some editors that invoke \TeX . This option used to be called `'-file-line-error-style'`.

`'-fmt=dumpname'`

`'-base=dumpname'`

`'-mem=dumpname'`

Use *dumpname* instead of the program name or a `'%&'` line to determine the name of the memory dump file read (`'fmt'` for \TeX , `'base'` for Metafont, `'mem'` for MetaPost). See Section 4.3 [Memory dumps], page 12. Also sets the program name to *dumpname* if no `'-programe'` option was given.

`'-halt-on-error'`

Stop processing and exit when an error occurs, as opposed to the normal process of trying to recover and continue.

`'-ini'` Enable the “initial” form of the program (see Section 4.2 [Initial and virgin], page 12). This is implicitly set if the program name is `initex` resp. `inimf`.

`'-interaction=string'`

Set the interaction mode from the command line. The *string* must be one of `'batchmode'`, `'nonstopmode'`, `'scrollmode'`, or `'errorstopmode'`.

`'-jobname=string'`

Set the job name to *string*, instead of deriving it from the name of the input file.

`'-kpathsea-debug=number'`

Set path searching debugging flags according to the bits of *number* (see Section “Debugging” in *Kpathsea*). You can also specify this in `KPATHSEA_DEBUG` environment variable (for all Web2c programs). (The command line value overrides.) The most useful value is `'-1'`, to get all available output.

`'-output-directory=dirname'`

Specify the directory *dirname* to which output files are written. Also look for input files in *dirname* first, before looking along the normal search path. See Section 3.4 [Output file location], page 9.

`'-parse-first-line'`

`'-no-parse-first-line'`

Check or disable checking whether the first line of the main input file starts with `'%&'`, and parse it if it does. This line can be used specify the format and/or a TCX file.

`'-programe=string'`

Set program (and memory dump) name to *string*. This may affect the search paths and other values used (see Section “Config files” in *Kpathsea*). Using this option is equivalent to making a link named *string* to the binary and then invoking the binary under that name. See Section 4.3 [Memory dumps], page 12.

‘-recorder’

Enable the filename recorder. This makes the program save a list of the opened files into a file with (by default) extension ‘.fls’. For Aleph, this option is always on, and the file has extension ‘.ofl’.

Ordinarily, the ‘.fls’ file is written to the same location as the ‘.log’ file, for example, respecting `-output-directory` if it is given (see Section 3.4 [Output file location], page 9). However, if T_EX processing is done on the command line (or in response to the ‘**’ prompt), the ‘.fls’ might be written to the current directory, or include an integer (the current pid), as in `texput1234.fls`. You can use `-jobname` to explicitly set the basename.

‘-translate-file=tcxfile’

Use *tcxfile* to define which characters are printable and translations between the internal and external character sets. Moreover, *tcxfile* can be explicitly declared in the first line of the main input file ‘`%& -translate-file=tcxfile`’. This is the recommended method for portability reasons. See Section 5.4.2 [TCX files], page 22.

‘-8bit’

This option specifies that by default all characters should be considered printable. If ‘`-translate-file`’ was given as well, then the TCX file may mark characters as non-printable. This is a no-op in engines natively supporting Unicode.

3.3 Path searching

All of the Web2c programs, including T_EX, which do path searching use the Kpathsea routines to do so. The precise names of the environment and configuration file variables which get searched for particular file formatted are therefore documented in the Kpathsea manual (see Section “Supported file formats” in *Kpathsea*). Reading `texmf.cnf` (see Section “Config files” in *Kpathsea*), invoking `mktex...` scripts (see Section “mktex scripts” in *Kpathsea*), and so on are all handled by Kpathsea.

The programs which read fonts make use of another Kpathsea feature: `texfonts.map`, which allows arbitrary aliases for the actual names of font files; for example, ‘`Times-Roman`’ for ‘`ptmr8r.tfm`’. The distributed (and installed by default) `texfonts.map` includes aliases for many widely available PostScript fonts by their PostScript names.

3.4 Output file location

All the programs generally follow the usual convention for output files. Namely, they are placed in the directory current when the program is run, regardless of any input file location; or, in a few cases, output is to standard output.

For example, if you run ‘`tex /tmp/foo`’, for example, the output will be in `./foo.dvi` and `./foo.log`, not `/tmp/foo.dvi` and `/tmp/foo.log`.

You can use the ‘`-output-directory`’ option to cause all output files that would normally be written in the current directory to be written in the specified directory instead. See Section 3.2 [Common options], page 7.

If the current directory is not writable, and ‘`-output-directory`’ is not specified, the main programs (T_EX, Metafont, MetaPost, and BibT_EX) make an exception: if the config

file or environment variable value `TEXMFOUTPUT` is set (it is not by default), output files are written to the directory specified.

`TEXMFOUTPUT` is also checked for input files, as `TEX` often generates files that need to be subsequently read; for input, no suffixes (such as `‘.tex’`) are added by default and no exhaustive path searching is done, the input name is simply checked as given.

4 Three programs: Metafont, MetaPost, and T_EX

T_EX, Metafont, and MetaPost have a number of features in common. Besides the ones here, command-line options and other commonalities are described in the previous section.

4.1 Runtime options

Besides the configure- and compile-time options described in the installation section (see Chapter 2 [Installation], page 3), you can control a number of parameters in the `texmf.cnf` runtime file read by Kpathsea (see Section “Config files” in *Kpathsea*).

The main purpose of `texmf.cnf` is to specify search paths, but array sizes and other options are also set there. Most are rather obscure. Here are a few of the more interesting values:

`'main_memory'`

Total words of memory available, for T_EX, Metafont, and MetaPost. Must remake the format file after changing.

`'extra_mem_bot'`

Extra space for “large” T_EX data structures (default 0): boxes, glue, break-points, et al. If you use PiCT_EX, you may well want to set this.

`'expand_depth'`

Limit on recursive expansion calls before T_EX aborts (default 10000). If a T_EX program does an unterminated recursive expansion, T_EX will dutifully expand macros until the system’s runtime stack overflows, typically with a segmentation fault (SIGSEGV). This parameter was introduced to minimize the chance of that unpleasant (though not dangerous) crash, instead allowing T_EX to quit with a more informative message.

The crash can still happen, though, if the system has an exceptionally small memory allocation for its stack. There is no quantitative way to determine the limit, and it does not seem worth implementing system-dependent heuristics to guess at the number, since it’s highly improbable that any real T_EX code will ever need more than 10000 recursive expansions (it has never happened). For the same reason, using the `libsigsegv` library (<https://gnu.org/s/libsigsegv>) does not seem worth the effort.

`'texmf_casefold_search'`

See Section “Casefolding search” in *Kpathsea*.

Ideally all arrays would be dynamically expanded as necessary, so the only limiting factor would be the amount of swap space available, or some configurable limit much larger than can currently be supported.

Unfortunately, implementing this is extremely difficult, as the fixed size of arrays is assumed in many places throughout the source code. These runtime limits are a practical compromise between the compile-time limits in previous versions, and truly dynamic arrays. (On the other hand, the Web2c BibT_EX implementation does do true dynamic reallocation of some arrays.)

Nowadays there is rarely a reason to modify the values. But if you do wish to modify `texmf.cnf`, in T_EX Live the best approach is to put your changes, and only your changes

at the top of the TL installation tree. That is, if the system `texmf.cnf` is installed in `/some/path/to/texlive/YYYY/texmf-dist/web2c/texmf.cnf` is put your custom settings in `/some/path/to/texlive/YYYY/texmf.cnf`, where `YYYY` is the year of installation (if you use that subdirectory; it's the default). That way, unrelated changes to the system `texmf.cnf` can happen with normal updates, without affecting your local values.

4.2 Initial and virgin

The T_EX and Metafont programs each have two main variants, called *initial* and *virgin*. MetaPost no longer makes this distinction.

The initial form is enabled if:

1. the `-ini` option was specified; or
2. the program name is `initex` resp. `inimf`; or
3. the first line of the main input file is `%&ini`;

otherwise, the virgin form is used.

The *virgin* form is the one generally invoked for production use. The first thing it does is read a memory dump (see Section 4.3.2 [Determining the memory dump to use], page 13), and then proceeds on with the main job.

The *initial* form is generally used only to create memory dumps (see the next section). It starts up more slowly than the virgin form, because it must do lengthy initializations that are encapsulated in the memory dump file.

4.3 Memory dumps

In typical use, T_EX and Metafont require a large number of macros to be predefined; therefore, they support *memory dump* files, which can be read much more efficiently than ordinary source code.

4.3.1 Creating memory dumps

The programs all create memory dumps in slightly idiosyncratic (though substantially similar) way, so we describe the details in separate sections (references below). The basic idea is to run the initial version of the program (see Section 4.2 [Initial and virgin], page 12), read the source file to define the macros, and then execute the `\dump` primitive.

Also, each program uses a different filename extension for its memory dumps, since although they are completely analogous they are not interchangeable (T_EX cannot read a Metafont memory dump, for example).

Here is a list of filename extensions with references to examples of creating memory dumps:

T_EX (`.fmt`) See Section 5.2 [Initial T_EX], page 19.

Metafont (`.base`) See Section 6.2 [Initial Metafont], page 28.

When making memory dumps, the programs read environment variables and configuration files for path searching and other values as usual. If you are making a new installation and have environment variables pointing to an old one, for example, you will probably run into difficulties.

4.3.2 Determining the memory dump to use

The virgin form (see Section 4.2 [Initial and virgin], page 12) of each program always reads a memory dump before processing normal source input. All three programs determine the memory dump to use in the same way:

1. If the first non-option command-line argument begins with ‘&’, the program uses the remainder of that argument as the memory dump name. For example, running ‘`tex \&super`’ reads `super.fmt`. (The backslash protects the ‘&’ against interpretation by the shell.)
2. If the ‘`-fmt`’ resp. ‘`-base`’ option is specified, its value is used.
3. If the ‘`-progrname`’ option is specified, its value is used.
4. If the first line of the main input file (which must be specified on the command line, not in response to ‘**’) is `%&dump`, and `dump` is an existing memory dump of the appropriate type, `dump` is used.

The first line of the main input file can also specify which character translation file is to be used: `%&-translate-file=tcxfile` (see Section 5.4.2 [TCX files], page 22).

These two roles can be combined: `%&dump -translate-file=tcxfile`. If this is done, the name of the dump must be given first.

5. Otherwise, the program uses the program invocation name, most commonly `tex` resp. `mf`. For example, if `latex` is a link to `tex`, and the user runs ‘`latex foo`’, `latex.fmt` will be used.

4.3.3 Hardware and memory dumps

By default, memory dump files are sharable between architectures of different types; specifically, on machines of different endianness (see Section “Byte order” in *GNU C Library*) and with different word sizes (4-byte `long` vs. 8-byte `long`). This is a feature of the Web2c implementation, and is not true of all T_EX implementations.

The script `tl-check-fmtshare` in the T_EX Live source tree (`Master/tlpkg/bin`) provides a relatively easy way to test that a `.fmt` built on the local host can be loaded by a T_EX engine built on some remote host.

If you specify ‘`--disable-dump-share`’ to `configure`, however, memory dumps will be endian-dependent. The reason to do this is speed. To achieve endian-independence, the reading of memory dumps on LittleEndian architectures, such as PC’s and DEC architectures, is somewhat slowed (all the multibyte values have to be swapped). Usually, this is not noticeable, and the advantage of being able to share memory dumps across all platforms at a site far outweighs the speed loss. But if you’re trying to squeeze out every possible bit of performance, you may wish to do this.

T_EXnically, even without ‘`--disable-dump-share`’, sharing of `.fmt` files cannot be guaranteed to work. Floating-point values are always written in native format, and hence will generally not be readable across platforms. Fortunately, T_EX uses floating point only to represent glue ratios, and none of the common formats (plain, L^AT_EX, AMST_EX, ...) do any glue setting at `.fmt`-creation time. Metafont does not use floating point in any dumped value at all.

Incidentally, different memory dump files will never compare equal byte-for-byte, because the programs dump the current date and time. So don’t be alarmed by a few bytes difference.

If you don't know what endianness your machine is, and you're curious, here is a little C program to tell you. (The `configure` script contains a similar program.) This is from the book *C: A Reference Manual*, by Samuel P. Harbison and Guy L. Steele Jr. (see Appendix B [References], page 56).

```
main ()
{
    /* Are we little or big endian? From Harbison&Steele. */
    union
    {
        long l;
        char c[sizeof (long)];
    } u;
    u.l = 1;
    if (u.c[0] == 1)
        printf ("LittleEndian\n");
    else if (u.c[sizeof (long) - 1] == 1)
        printf ("BigEndian\n");
    else
        printf ("unknownEndian");

    exit (u.c[sizeof (long) - 1] == 1);
}
```

You can add `printf("long %d\n", sizeof(long));` to see the size of the `long` data type.

4.4 Editor invocation

T_EX, Metafont, and MetaPost all (by default) stop and ask for user intervention at an error. If the input came from a file, and the user responds with `e` or `E`, the program invokes an editor.

Specifying `'--with-editor=cmd'` to `configure` sets the default editor command string to `cmd`. The environment variables/configuration values `TEXEDIT`, `MFEDIT`, and `MPEDIT` (respectively) override this. If `'--with-editor'` is not specified, the default is `vi +%d %s` on Unix, and an invocation of the T_EXworks editor on Windows. (See `texmf.cnf` for the precise values.)

In this string, `'%d'` is replaced by the line number of the error, and `'%s'` is replaced by the name of the current input file.

4.5 `\input` filenames

T_EX, Metafont, and MetaPost source programs can all read other source files with the `\input` (T_EX) and `input` (MF and MP) primitives:

```
\input name % in TeX
```

The file `name` can always be terminated with whitespace; for Metafont and MetaPost, the statement terminator `';` also works. (L^AT_EX and other macro packages provide other interfaces to `\input` that allow different notation; here we are concerned only with the primitive operation.)

As (allowed) extensions to standard T_EX, Web2c also supports specifying the filename in double quotes ("some name") and in braces ({some name}), which is convenient for filenames containing spaces or other special characters, as described in the sections below.

In all cases, space tokens are ignored after the filename is read.

Also, double quote (") characters are ignored within the filename; there is no way to read files whose names contain a ".

However, for maximal portability of your document across systems, use only the characters ‘a’–‘z’, ‘0’–‘9’, and at most one ‘.’. Do not use anything but simple filenames, since directory separators vary among systems; instead, add the necessary directories to the appropriate search path.

4.5.1 `\input` quoted filename: `\input "some name"`

As of Web2c version 7.5.3 (2004), double-quote characters can be used to include spaces or other special characters. In typical use, the “” characters surround the entire filename:

```
\input "filename with spaces"
```

Technically, the quote characters can be used inside the name, and can enclose any characters, as in:

```
\input filename" "with" "spaces"
```

One more point. In L^AT_EX, the quotes are needed inside the braces of its `\input` macro, thus:

```
\input{a b}      % fails
\input{"a b"}    % ok
```

There is no way to quote the quote character.

4.5.2 `\input` braced filename: `\input{some name}`

As of Web2c 2020, `\input` filenames in T_EX engines (this does not apply in Metafont and MetaPost) can also be specified within a T_EX group, typically curly braces. For example:

```
\input{filename with spaces}
```

As always with T_EX, the brace characters are not hardwired; what counts is the category code: the first token after the `\input` must be of catcode 1 (begin group), and it is matched with the next character of catcode 2 (end group).

Within the group-delimited filename, braces are treated as normal characters.

As with all forms of filenames, following spaces are ignored (after the end group), and double quote (") characters are ignored within the filename.

4.5.3 `\input` filename caveats

The quoting mechanisms just described come into play *after* T_EX has tokenized and expanded the input. So, multiple spaces and tabs will generally be seen as a single space, active characters such as ‘~’ are expanded first (generally causing an error), and so on. More examples below.

On the other hand, various C library routines and Unix itself use the null byte (character code zero, ASCII NUL) to terminate strings. So filenames in Web2c cannot contain nulls, even though T_EX itself does not treat NUL specially.

Finally, the present Web2c implementation does ‘~’ and ‘\$’ expansion on *name*, unlike Knuth’s original implementation. Thus:

```
\input ~jsmith/$foo.bar
```

will dereference the environment variable or Kpathsea config file value ‘foo’ and read that file, extended with ‘.bar’, in user ‘jsmith’’s home directory. You can also use braces in the variable expansion, as in ‘\${foo}bar’, if you want to follow the variable name with a letter, numeral, or ‘_’.

(So another way to get a program to read a filename containing whitespace is to define an environment variable and dereference it.)

In all the common T_EX formats (plain T_EX, L^AT_EX, ConT_EXt, AMST_EX, . . .), the characters ‘~’ and ‘\$’ have special category codes, so to actually use these in a document you have to change their catcodes or use `\string`.

5 T_EX: Typesetting

T_EX is a typesetting system: it was especially designed to handle complex mathematics, as well as most ordinary text typesetting.

T_EX is a batch language, like C or Pascal, and not an interactive “word processor”: you compile a T_EX input file into a corresponding device-independent (DVI) file (and then translate the DVI file to the commands for a particular output device). This approach has both considerable disadvantages and considerable advantages. For a complete description of the T_EX language, see *The T_EXbook* (see Appendix B [References], page 56). Many other books on T_EX, introductory and otherwise, are available.

5.1 tex invocation

T_EX (usually invoked as `tex`) formats the given text and commands, and outputs a corresponding device-independent representation of the typeset document. This section merely describes the options available in the Web2c implementation. For a complete description of the T_EX typesetting language, see *The T_EXbook* (see Appendix B [References], page 56).

T_EX, Metafont, and MetaPost process the command line (described here) and determine their memory dump (fmt) file in the same way (see Section 4.3 [Memory dumps], page 12). Synopses:

```
tex [option]... [texname[.tex]] [tex-commands]
tex [option]... \first-line
tex [option]... &fmt args
```

T_EX searches the usual places for the main input file *texname* (see Section “Supported file formats” in *Kpathsea*), extending *texname* with `.tex` if necessary. To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

After *texname* is read, T_EX processes any remaining *tex-commands* on the command line as regular T_EX input. Also, if the first non-option argument begins with a T_EX escape character (usually `\`), T_EX processes all non-option command-line arguments as a line of regular T_EX input.

If no arguments or options are specified, T_EX prompts for an input file name with ‘**’.

T_EX writes the main DVI output to the file *basetexname.dvi*, where *basetexname* is the basename of *texname*, or ‘`texput`’ if no input file was specified. A DVI file is a device-independent binary representation of your T_EX document. The idea is that after running T_EX, you translate the DVI file using a separate program to the commands for a particular output device, such as a PostScript printer (see Section “Introduction” in *Dvips*) or an X Window System display (see `xdvi(1)`).

T_EX also reads TFM files for any fonts you load in your document with the `\font` primitive. By default, it runs an external program named `mktexfm` to create any nonexistent TFM files. You can disable this at configure-time or runtime (see Section “mktex configuration” in *Kpathsea*). This is enabled mostly for the sake of the EC fonts, which can be generated at any size.

T_EX can write output files, via the `\openout` primitive; this opens a security hole vulnerable to Trojan horse attack: an unwitting user could run a T_EX program that overwrites, say, `~/rhosts`. (MetaPost has a `write` primitive with similar implications). To alleviate

this and similar problems the functions `kpathsea_out_name_ok` and `kpathsea_in_name_ok` from the Kpathsea library (see Section “Calling sequence” in *Kpathsea*) are used to determine if a given filename is acceptable to be opened for output or input, depending on the setting of the configuration variables `openout_any` and `openin_any`: ‘a’ (for “any”, the default for `openin_any`), ‘r’ (for “restricted”), or ‘p’ (for “paranoid”, the default for `openout_any`).

In any case, all `\openout` filenames are recorded in the log file, except those opened on the first line of input, which is processed when the log file has not yet been opened.

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 7):

- ‘-enc’
- ‘-[no]-file-line-error’
- ‘-fmt=*fmtname*’
- ‘-halt-on-error’
- ‘-ini’
- ‘-interaction=*string*’
- ‘-ipc’
- ‘-ipc-start’
- ‘-jobname=*string*’
- ‘-kpathsea-debug=*number*’
- ‘-[no]parse-first-line’
- ‘-output-directory’
- ‘-progname=*string*’
- ‘-recorder’
- ‘-translate-file=*tcxfile*’
- ‘-8bit’ These options are common to T_EX, Metafont, and MetaPost. See Section 3.2 [Common options], page 7.
- ‘-enc’ Enable encT_EX extensions, such as `\mubyte`. This can be used to support the Unicode UTF-8 input encoding, although using an engine with native Unicode support is more common nowadays. <http://www.olsak.net/encTex.html>.
- ‘-ipc’
- ‘-ipc-start’
- With either option, T_EX writes its DVI output to a socket as well as to the usual `.dvi` file. With ‘-ipc-start’, T_EX also opens a server program at the other end to read the output. See Section 5.6 [IPC and T_EX], page 25.
- These options are available only if the ‘--enable-ipc’ option was specified to `configure` during installation of Web2c.
- ‘-mktex=*filetype*’
- ‘-no-mktex=*filetype*’
- Turn on or off the ‘mktex’ script associated with *filetype*. For T_EX proper, *filetype* can only be ‘tex’ and ‘tfm’, but for pdfT_EX and luaT_EX, it can also be ‘pk’.
- ‘-mltex’ If we are INITEX (see Section 4.2 [Initial and virgin], page 12), enable MLT_EX extensions such as `\charsubdef`. Implicitly set if the program name is `mltex`. See Section 5.4.1 [MLT_EX], page 21.

`'-output-comment=string'`

Use *string* as the DVI file comment. Ordinarily, this comment records the date and time of the T_EX run, but if you are doing regression testing, you may not want the DVI file to have this spurious difference. This is also taken from the environment variable and config file value `'output_comment'`.

`'-shell-escape'`

`'-no-shell-escape'`

`'-shell-restricted'`

Enable, or disable, or enable with restrictions the `\write18{shell-command}` feature for external executing shell commands. See Section 5.5 [Shell escapes], page 24.

`'-enable-write18'`

`'-disable-write18'`

Synonyms for `-shell-escape` and `-no-shell-escape`, for compatibility with MiK_TE_X. (MiK_TE_X also accepts both pairs of options.) See Section 5.5 [Shell escapes], page 24.

`'-src-specials'`

`'-src-specials=string'`

This option makes T_EX output specific source information using `\special` commands in the DVI file. These `\special` track the current file name and line number.

Using the first form of this option, the `\special` commands are inserted automatically.

In the second form of the option, *string* is a comma separated list of the following values: `'cr'`, `'display'`, `'hbox'`, `'math'`, `'par'`, `'parent'`, `'vbox'`. You can use this list to specify where you want T_EX to output such commands. For example, `'-src-specials=cr,math'` will output source information every line and every math formula.

These commands can be used with the appropriate DVI viewer and text editor to switch from the current position in the editor to the same position in the viewer and back from the viewer to the editor.

This option works by inserting `\special` commands into the token stream, and thus in principle these additional tokens can be recovered or seen by the tricky-enough macros. If you run across a case, let us know, because this counts as a bug. However, such bugs are very hard to fix, requiring significant changes to T_EX, so please don't count on it.

Redefining `\special` will not affect the functioning of this option. The commands inserted into the token stream are hard-coded to always use the `\special` primitive.

T_EX does not pass the trip test when this option is enabled.

5.2 Initial T_EX

The *initial* form of T_EX is invoked by `'tex -ini'`. It does lengthy initializations avoided by the “virgin” (`vir`) form, so as to be capable of dumping `'fmt'` files (see Section 4.3

[Memory dumps], page 12). For a detailed comparison of virgin and initial forms, see Section 4.2 [Initial and virgin], page 12.

For a list of options and other information, see Section 5.1 [tex invocation], page 17.

Unlike Metafont and MetaPost, many format files are commonly used with T_EX. The standard one implementing the features described in the *T_EXbook* is ‘plain.fmt’, also known as ‘tex.fmt’ (again, see Section 4.3 [Memory dumps], page 12). It is created by default during installation, but you can also do so by hand if necessary (e.g., if an update to plain.tex is issued):

```
tex -ini '\input plain \dump'
```

(The quotes prevent interpretation of the backslashes from the shell.) Then install the resulting plain.fmt in ‘\$(fmdir)’ (/usr/local/share/texmf/web2c by default), and link tex.fmt to it.

The necessary invocation for generating a format file differs for each format, so instructions that come with the format should explain. The top-level web2c Makefile has targets for making most common formats: plain latex amstex texinfo eplain. See Section 5.3 [Formats], page 20, for more details on T_EX formats.

5.3 Formats

T_EX *formats* are large collections of macros, often dumped into a .fmt file (see Section 4.3 [Memory dumps], page 12) by `tex -ini` (see Section 5.2 [Initial TeX], page 19). A number of formats are in reasonably widespread use, and the Web2c Makefile has targets to make the versions current at the time of release. You can change which formats are automatically built by setting the `fmts` Make variable; by default, only the ‘plain’ and ‘latex’ formats are made.

Nowadays, the formats are generally installed and updated as part of a larger T_EX distribution, such as T_EX Live (<https://tug.org/texlive>).

- latex** The most widely used format. The current release is named ‘L^AT_EX2e’; new versions are released approximately every six months, with patches issued as needed. The old release was called ‘L^AT_EX 2.09’, and is no longer maintained or supported. L^AT_EX attempts to provide generic markup instructions, such as “emphasize”, instead of specific typesetting instructions, such as “use the 10pt Computer Modern italic font”. The L^AT_EX home page: <https://www.latex-project.org>.
- context** ConT_EXt is an independent macro package which has a basic document structuring approach similar to L^AT_EX. It also supports creating interactive PDF files and has integrated MetaPost support, among many other interesting features. The ConT_EXt home page: <http://www.pragma-ade.com>.
- amstex** The official typesetting system of the American Mathematical Society. Like L^AT_EX, it encourages generic markup commands. The AMS also provides many L^AT_EX packages for authors who prefer L^AT_EX. Taken together, they are used to produce nearly all AMS publications, e.g., *Mathematical Reviews*. The AMST_EX home page: <https://www.ams.org/tex>.
- texinfo** The documentation system developed and maintained by the Free Software Foundation for their software manuals. It can be automatically converted into

- plain text, a machine-readable on-line format called ‘info’, HTML, etc. The Texinfo home page: <https://www.gnu.org/software/texinfo>.
- eplain** The “expanded plain” format provides various common features (e.g., symbolic cross-referencing, tables of contents, indexing, citations using BibT_EX), for those authors who prefer to handle their own high-level formatting. The Eplain home page: <https://tug.org/eplain>.
- slitex** An obsolete L^AT_EX 2.09 format for making slides. It is replaced by the ‘slides’ document class, although the ‘beamer’ package is the most commonly method for making slides nowadays. The Beamer page on CTAN: <https://ctan.org/pkg/beamer>.

5.4 Languages and hyphenation

T_EX supports most natural languages. See also Section 5.7 [T_EX extensions], page 25.

5.4.1 MLT_EX: Multi-lingual T_EX

Multi-lingual T_EX (`mltex`) is an extension of T_EX originally written by Michael Ferguson and now updated and maintained by Bernd Raichle. With the advent of Unicode, it has become obsolete, though it is still supported in Web2c in the event of bugs or compilation bugs.

MLT_EX allows the use of non-existing glyphs in a font by declaring glyph substitutions. These are restricted to substitutions of an accented character glyph, which need not be defined in the current font, by its appropriate `\accent` construction using a base and accent character glyph, which do have to exist in the current font. This substitution is automatically done behind the scenes, if necessary, and thus MLT_EX additionally supports hyphenation of words containing an accented character glyph for fonts missing this glyph (e.g., Computer Modern). Standard T_EX suppresses hyphenation in this case.

MLT_EX works at `.fmt`-creation time: the basic idea is to specify the ‘`-mltex`’ option to T_EX when you `\dump` a format. Then, when you subsequently invoke T_EX and read that `.fmt` file, the MLT_EX features described below will be enabled.

Generally, you use special macro files to create an MLT_EX `.fmt` file.

The sections below describe the two new primitives that MLT_EX defines. Aside from these, MLT_EX is completely compatible with standard T_EX.

5.4.1.1 `\charsubdef`: Character substitutions

The most important primitive MLT_EX adds is `\charsubdef`, used in a way reminiscent of `\chardef`:

```
\charsubdef composite [=] accent base
```

Each of *composite*, *accent*, and *base* are font glyph numbers, expressed in the usual T_EX syntax: ‘`\e` symbolically, ‘145 for octal, “65 for hex, 101 for decimal.

MLT_EX’s `\charsubdef` declares how to construct an accented character glyph (not necessarily existing in the current font) using two character glyphs (that do exist). Thus it defines whether a character glyph code, either typed as a single character or using the `\char` primitive, will be mapped to a font glyph or to an `\accent` glyph construction.

For example, if you assume glyph code 138 (decimal) for an e-circumflex (ê) and you are using the Computer Modern fonts, which have the circumflex accent in position 18 and lowercase ‘e’ in the usual ASCII position 101 decimal, you would use `\charsubdef` as follows:

```
\charsubdef 138 = 18 101
```

For the plain T_EX format to make use of this substitution, you have to redefine the circumflex accent macro `\^` in such a way that if its argument is character ‘e’ the expansion `\char138` is used instead of `\accent18 e`. Similar `\charsubdef` declaration and macro redefinitions have to be done for all other accented characters.

To disable a previous `\charsubdef c`, redefine `c` as a pair of zeros. For example:

```
\charsubdef '321 = 0 0 % disable N tilde
```

(Octal '321 is the ISO Latin-1 value for the Spanish N tilde.)

`\charsubdef` commands should only be given once. Although in principle you can use `\charsubdef` at any time, the result is unspecified. If `\charsubdef` declarations are changed, usually either incorrect character dimensions will be used or MLT_EX will output missing character warnings. (The substitution of a `\charsubdef` is used by T_EX when appending the character node to the current horizontal list, to compute the width of a horizontal box when the box gets packed, and when building the `\accent` construction at `\shipout`-time. In summary, the substitution is accessed often, so changing it is not desirable, nor generally useful.)

5.4.1.2 `\tracingcharsubdef`: Substitution diagnostics

To help diagnose problems with `\charsubdef`, MLT_EX provides a new primitive parameter, `\tracingcharsubdef`. If positive, every use of `\charsubdef` will be reported. This can help track down when a character is redefined.

In addition, if the T_EX parameter `\tracinglostchars` is 100 or more, the character substitutions actually performed at `\shipout`-time will be recorded.

5.4.2 TCX files: Character translations

TCX (T_EX character translation) files help T_EX support direct input of 8-bit international characters if fonts containing those characters are being used. Specifically, they map an input (keyboard) character code to the internal T_EX character code (a superset of ASCII).

Of the various proposals for handling more than one input encoding, TCX files were chosen because they follow Knuth’s original ideas for the use of the ‘`xchr`’ and ‘`xord`’ tables. He ventured that these would be changed in the WEB source in order to adjust the actual version to a given environment. It turns out, however, that recompiling the WEB sources is not as simple a task as Knuth may have imagined; therefore, TCX files, providing the possibility of changing of the conversion tables on on-the-fly, have been implemented instead.

This approach limits the portability of T_EX documents, as some implementations do not support it (or use a different method for input-internal reencoding). It may also be problematic to determine the encoding to use for a T_EX document of unknown provenance; in the worst case, failure to do so correctly may result in subtle errors in the typeset output. But we feel the benefits outweigh these disadvantages.

This is entirely independent of the MLT_EX extension (see Section 5.4.1 [MLT_EX], page 21): whereas a TCX file defines how an input keyboard character is mapped to T_EX's internal code, MLT_EX defines substitutions for a non-existing character glyph in a font with a `\accent` construction made out of two separate character glyphs. TCX files involve no new primitives; it is not possible to specify that an input (keyboard) character maps to more than one character.

Information on specifying TCX files:

- The best way to specify a TCX file is to list it explicitly in the first line of the main document:

```
%& -translate-file=tcxfile
```

- You can also specify a TCX file to be used on a particular T_EX run with the command-line option `'-translate-file=tcxfile'`.
- TCX files are searched for along the WEB2C path.
- Initial T_EX (see Section 5.2 [Initial T_EX], page 19) ignores TCX files.

The Web2c distribution comes with a number of TCX files. Two important ones are `il1-t1.tcx` and `il2-t1.tcx`, which support ISO Latin 1 and ISO Latin 2, respectively, with Cork-encoded fonts (a.k.a. the L^AT_EX T1 encoding). TCX files for Czech, Polish, and Slovak are also provided.

One other notable TCX file is `empty.tcx`, which is, well, empty. Its purpose is to reset Web2C's behavior to the default (only visible ASCII being printable, as described below) when a format was dumped with another TCX being active—which is in fact the case for everything but plain T_EX in the TeX Live and other distributions. Thus:

```
latex somefile8.tex
⇒ terminal etc. output with 8-bit chars
latex --translate-file=empty.tcx somefile8.tex
⇒ terminal etc. output with ^^ notation
```

Syntax of TCX files:

1. Line-oriented. Blank lines are ignored.
2. Whitespace is ignored except as a separator.
3. Comments start with `'%'` and continue to the end of the line.
4. Otherwise, a line consists of one or two character codes, optionally followed by 0 or 1. The last number indicates whether *dest* is considered printable.

```
src [dest [prnt]]
```

5. Each character code may be specified in octal with a leading `'0'`, hexadecimal with a leading `'0x'`, or decimal otherwise. Values must be between 0 and 255, inclusive (decimal).
6. If the *dest* code is not specified, it is taken to be the same as *src*.
7. If the same *src* code is specified more than once, it is the last definition that counts.

Finally, here's what happens: when T_EX sees an input character with code *src*, it 1) changes *src* to *dest*; and 2) makes the *dest* code “printable”, i.e., printed as-is in diagnostics and the log file rather than in `'^^'` notation.

By default, no characters are translated, and character codes between 32 and 126 inclusive (decimal) are printable.

Specifying translations for the printable ASCII characters (codes 32–127) will yield unpredictable results. Additionally you shouldn't make the following characters printable: `^^I` (TAB), `^^J` (line feed), `^^M` (carriage return), and `^^?` (delete), since T_EX uses them in various ways.

Thus, the idea is to specify the input (keyboard) character code for *src*, and the output (font) character code for *dest*.

By default, only the printable ASCII characters are considered printable by T_EX. If you specify the `-8bit` option, all characters are considered printable by default. If you specify both the `-8bit` option and a TCX file, then the TCX can set specific characters to be non-printable.

Both the specified TCX encoding and whether characters are printable are saved in the dump files (like `tex.fmt`). So by giving these options in combination with `-ini`, you control the defaults seen by anyone who uses the resulting dump file.

When loading a dump, if the `-8bit` option was given, then all characters become printable by default.

When loading a dump, if a TCX file was specified, then the TCX data from the dump is ignored and the data from the file used instead.

5.4.3 Patgen: Creating hyphenation patterns

Patgen creates hyphenation patterns from dictionary files for use with T_EX. Synopsis:

```
patgen dictionary patterns output translate
```

Each argument is a filename. No path searching is done. The output is written to the file *output*.

In addition, Patgen prompts interactively for other values.

For more information, see *Word hyphen-a-tion by com-put-er* by Frank Liang (see Appendix B [References], page 56), and also the `patgen.web` source file.

The only options are `-help` and `-version` (see Section 3.2 [Common options], page 7).

5.5 Shell escapes

T_EX can execute *shell escapes*, that is, arbitrary shell commands. Although tremendously useful, this also has obvious security implications. Therefore, as of T_EX Live 2009, a *restricted* mode for shell escapes is the default mode of operation, which allows executing only certain commands, as specified in the `texmf.cnf` configuration file.

- Unrestricted shell escapes are allowed if the option `--shell-escape` is specified, or if the environment variable or config file value `shell_escape` is set to `'t'` or `'y'` and `'1'`.
- Restricted shell escapes are allowed if `shell_escape` is set to `'p'`. This is the default.
- Shell escapes are completely disabled if `--no-shell-escape` is specified, or if `shell_escape` is set to anything else.

When enabled, the T_EX construct to execute a system command is `\write18{shell-command}`; for example:

```
\write18{echo "hello, world"}
```

From T_EX's point of view, this is a normal `\write` command, and is therefore subject to the usual T_EX expansions. Also, the system call either happens during the `\output` routine or right away, according to the absence or presence of the `\immediate` prefix, as usual for `\write`.

The *shell-command* string is passed to the command shell (via the C library function `system`). The output of *shell-command* is not diverted anywhere, so it will not appear in the log file, or anywhere but the terminal output. The exit status of the system call is also not available to T_EX.

In unrestricted mode, the argument is simply passed straight to `system` unaltered.

In restricted mode, ASCII double quote characters (") should always be used in the argument to `\write18` where quoting of arguments is needed, as in the example above. This is to achieve some measure of system independence. On Unix systems, these are replaced with single quote (') characters to avoid insecure further expansion. Care is also taken on Windows to avoid additional expansions (from, e.g., `'...'`). Mismatched quotation marks in the command string result in a diagnostic message in the log file; no execution is performed.

After quotation processing, if the first word (delimited by a space or tab) of the command is in the list specified by the `shell_escape_commands` configuration value, the command is executed. Otherwise it is not. In any case, a message is written to the log file.

The `shell_escape_commands` value is a comma-separated list of words. Whitespace is significant, and typically should not be present. The default definition in `texmf.cnf` looks like this, but with more commands included:

```
shell_escape_commands = bibtex,kpsewhich,repstopdf,...
```

pdfT_EX and luaT_EX support reading (via `\input` and `\openin`) and writing (via `\openout`) from pipes if the first character is '|'. The following command is then treated exactly the same as the argument to `\write18`. In these engines, the primitive variable `\pdfshellescape` is set to 0 if shell escapes are disabled, 1 if they are enabled, and 2 if they are enabled with restrictions.

The purpose of this feature is to make it possible for T_EX documents to perform useful external actions in the common case of an individual user running a known document on his or her own machine. In such environments as CGI scripts or wikis where the input has to be considered untrustworthy, shell escapes should be completely disabled.

5.6 IPC and T_EX

(If anyone uses this feature and needs documentation, write tex-k@tug.org.)

This functionality is available only if the `--enable-ipc` option was specified to `configure` during installation of Web2c (see Chapter 2 [Installation], page 3).

If you define `IPC_DEBUG` before compilation (e.g., with `'make XCFLAGS=-DIPC_DEBUG'`), T_EX will print messages to standard error about its socket operations. This may be helpful if you are, well, debugging.

5.7 Extended T_EX engines

The base T_EX program has been extended in many ways.

There has been a substantial effort to make a set of extended functionality available across all actively-updated engines, so that formats, notably L^AT_EX, can rely on it. A list of this common extended functionality is in a L^AT_EX News article, <https://www.latex-project.org/news/latex2e-news/1tnews31.pdf>. For engines in T_EX Live, the detailed documentation for these primitives is mostly in the pdfT_EX manual (<http://pdftex.org>).

In addition, each engine (naturally) has its own particular features, described in its own manual. Here's a partial list of the engines.

- e-T_EX Adds many new primitives, including right-to-left typesetting and more registers. Now frozen. More info: <https://ctan.org/pkg/etex>.
- Aleph This adds Unicode support, right-to-left typesetting, and more, based on the Omega engine, with the e-T_EX and other extensions. Aleph is maintained only for serious bug fixes and does not include the common functionality mentioned above. More info: <https://ctan.org/pkg/aleph>, <https://ctan.org/pkg/omega>.
- pdfT_EX Can produce PDF as well as DVI files. It also incorporates the e-T_EX extensions, new primitives for hypertext and micro-typography, reading/writing from pipes, and much more. In T_EX Live, the command `etex` invokes pdfT_EX to make all these additions available with DVI output. Home page: <http://pdftex.org>.
- LuaT_EX Embeds the Lua programming language (<http://lua.org>) and opens up the T_EX typesetting engine to control from Lua, starting from the pdfT_EX capabilities as a base. Also natively supports UTF-8 input, the OpenType and TrueType font formats, and use of system fonts. Home page: <http://luatex.org>.
- XeT_EX Combines support for Unicode input, the OpenType and TrueType font formats, and use of system fonts with the capabilities of pdfT_EX, with the exception of the font expansion part of micro-typography. Home page: <https://tug.org/xetex>.
- hiT_EX Outputs its own HINT format, which is designed for reading technical documents on mobile devices. More info: <https://ctan.org/pkg/hitex>.
- pT_EX
upT_EX With additional support for Japanese; pT_EX was the original engine, and upT_EX has native Unicode support and thus is more useful for Chinese and Korean. More info: <https://ctan.org/pkg/ptex>, <https://ctan.org/pkg/uptex>.
- epT_EX
eupT_EX Further extends pT_EX and upT_EX with the e-T_EX extensions. More info: <https://ctan.org/pkg/eptex>, <https://ctan.org/pkg/euptex>.

6 Metafont: Creating typeface families

Metafont is a system for producing shapes; it was designed for producing complete typeface families, but it can also produce geometric designs, dingbats, etc. And it has considerable mathematical and equation-solving capabilities which can be useful entirely on their own.

Metafont is a batch language, like C or Pascal: you compile a Metafont program into a corresponding font, rather than interactively drawing lines or curves. This approach has both considerable disadvantages (people unfamiliar with conventional programming languages will be unlikely to find it usable) and considerable advantages (you can make your design intentions specific and parameterizable). For a complete description of the Metafont language, see *The METAFONTbook* (see Appendix B [References], page 56).

6.1 mf invocation

Metafont (usually invoked as `mf`) reads character definitions specified in the Metafont programming language, and outputs the corresponding font. This section merely describes the options available in the Web2c implementation. For a complete description of the Metafont language, see *The Metafontbook* (see Appendix B [References], page 56).

Metafont processes its command line and determines its memory dump (base) file in a way exactly analogous to MetaPost and T_EX (see Section 5.1 [tex invocation], page 17, and see Section 4.3 [Memory dumps], page 12). Synopses:

```
mf [option]... [mfname[.mf]] [mf-commands]
mf [option]... \first-line
mf [option]... &base args
```

Most commonly, a Metafont invocation looks like this:

```
mf '\mode:=mode; mag:=magnification; input mfname'
```

(The single quotes avoid unwanted interpretation by the shell.)

Metafont searches the usual places for the main input file *mfname* (see Section “Supported file formats” in *Kpathsea*), extending *mfname* with `.mf` if necessary. To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to `-1` before running the program. By default, Metafont runs an external program named `mktxmf` to create any nonexistent Metafont source files you input. You can disable this at configure-time or runtime (see Section “mktex configuration” in *Kpathsea*). This is mostly for the sake of the EC fonts, which can be generated at any size.

Metafont writes the main GF output to the file *basemfname.nnn*gf, where *nnn* is the font resolution in pixels per inch, and *basemfname* is the basename of *mfname*, or `mfput` if no input file was specified. A GF file contains bitmaps of the actual character shapes. Usually GF files are converted immediately to PK files with `GFtoPK` (see Section 11.2 [gftopk invocation], page 47), since PK files contain equivalent information, but are more compact. (Metafont output in GF format rather than PK for only historical reasons.)

Metafont also usually writes a metric file in TFM format to *basemfname.tfm*. A TFM file contains character dimensions, kerns, and ligatures, and spacing parameters. T_EX reads only this `.tfm` file, not the GF file.

The *mode* in the example command above is a name referring to a device definition (see Section 6.3 [Modes], page 29); for example, `localfont` or `ljfour`. These device definitions

must generally be precompiled into the base file. If you leave this out, the default is proof mode, as stated in *The Metafontbook*, in which Metafont outputs at a resolution of 2602 dpi; this is usually not what you want. The remedy is simply to assign a different mode—`localfont`, for example.

The *magnification* assignment in the example command above is a magnification factor; for example, if the device is 600 dpi and you specify `mag:=2`, Metafont will produce output at 1200 dpi. Very often, the *magnification* is an expression such as `magstep(.5)`, corresponding to a T_EX “magstep”, which are factors of $1.2\sqrt{2}$.

After running Metafont, you can use the font in a T_EX document as usual. For example:

```
\font\myfont = newfont
\myfont Now I am typesetting in my new font (minimum hamburgers).
```

The program accepts the following options, as well as the standard ‘`-help`’ and ‘`-version`’ (see Section 3.2 [Common options], page 7):

```
‘-[no]-file-line-error’
‘-fmt=fmtname’
‘-halt-on-error’
‘-ini’
‘-interaction=string’
‘-jobname=string’
‘-kpathsea-debug=number’
‘-[no]parse-first-line’
‘-output-directory’
‘-progname=string’
‘-recorder’
‘-translate-file=tcxfile’
‘-8bit’
‘-mktex=filetype’
‘-no-mktex=filetype’
```

These options are common to T_EX, Metafont, and MetaPost. See Section 3.2 [Common options], page 7.

Turn on or off the ‘`mktex`’ script associated with *filetype*. The only value that makes sense for *filetype* is ‘`mf`’.

6.2 Initial Metafont

`inimf` is the “initial” form of Metafont, which does lengthy initializations avoided by the “virgin” (`vir`) form, so as to be capable of dumping ‘`.base`’ files (see Section 4.3 [Memory dumps], page 12). For a detailed comparison of virgin and initial forms, see Section 4.2 [Initial and virgin], page 12.

For a list of options and other information, see Section 6.1 [mf invocation], page 27.

The only memory dump file commonly used with Metafont is the default ‘`plain.base`’, also known as ‘`mf.base`’ (again, see Section 4.3 [Memory dumps], page 12). It is created by default during installation, but you can also do so by hand if necessary (e.g., if a Metafont update is issued):

```
mf -ini '\input plain; input modes; dump'
```


(The quotes prevent interpretation of the backslashes from the shell.) Then install the resulting `plain.base` in `'$(basedir)'` (`/usr/local/share/texmf/web2c` by default), and link `mf.base` to it.

For an explanation of the additional `modes.mf` file, see Section 6.3 [Modes], page 29. This file has no counterpart in T_EX or MetaPost.

In the past, it was sometimes useful to create a base file `cmmf.base` (a.k.a. `cm.base`), with the Computer Modern macros also included in the base file. Nowadays, however, the additional time required to read `cmbase.mf` is exceedingly small, usually not enough to be worth the administrative hassle of updating the `cmmf.base` file when you install a new version of `modes.mf`. People actually working on a typeface may still find it worthwhile to create their own base file, of course.

6.3 Modes: Device definitions for Metafont

Running Metafont and creating Metafont base files requires information that T_EX and MetaPost do not: *mode* definitions which specify device characteristics, so Metafont can properly rasterize the shapes.

When making a base file, a file containing modes for locally-available devices should be input after `plain.mf`. One commonly used file is `ftp://ftp.tug.org/tex/modes.mf`; it includes all known definitions.

If, however, for some reason you have decreased the memory available in your Metafont, you may need to copy `modes.mf` and remove the definitions irrelevant to you (probably most of them) instead of using it directly. (Or, if you're a Metafont hacker, maybe you can suggest a way to redefine `mode_def` and/or `mode_setup`; right now, the amount of memory used is approximately four times the total length of the `mode_def` names, and that's a lot.)

If you have a device not included in `modes.mf`, please see comments in that file for how to create the new definition, and please send the definition to `tex-fonts@math.utah.edu` to get it included in the next release of `modes.mf`.

Usually, when you run Metafont you must supply the name of a mode that was dumped in the base file. But you can also define the mode characteristics dynamically, by invoking Metafont with an assignment to `smode` instead of `mode`, like this:

```
mf '\smode:="newmode.mf"; mag:=magnification; input mfname'
```

This is most useful when you are working on the definition of a new mode.

The *magnification* and *mfname* arguments are explained in Section 6.1 [mf invocation], page 27. In the file `newmode.mf`, you should have the following (with no `mode_def` or `enddef`), if you are using `modes.mf` conventions:

```
mode_param (pixels_per_inch, dpi);
mode_param (blacker, b);
mode_param (fillin, f);
mode_param (o_correction, o);
mode_common_setup_;
```

(Of course, you should use real numbers for *dpi*, *b*, *f*, and *o*.)

For more information on the use of `smode`, or if you are not using `modes.mf`, see page 269 of *The Metafontbook*.

6.4 Online Metafont graphics

The Web2c implementation of Metafont can do online graphics with a number of devices. (See the Metafont manual for more information about how to draw on your screen.) By default, no graphics support is enabled.

Metafont examines the `MFTERM` environment variable or config file value at runtime, or the `TERM` environment variable if `MFTERM` is not set, to determine the device support to use. Naturally, only the devices for which support has been compiled in can be selected.

Here is a table of the possibilities, showing the `MFTERM` value and the corresponding `configure` option(s) in parentheses.

<code>epsf</code>	(<code>--enable-epsfwin</code>) Pseudo-window server for Encapsulated PostScript (see <code>web2c/window/epsf.c</code>). This device produces an EPS file containing the graphics which would be displayed online on other devices. The name of the EPS file defaults to <code>metafont.eps</code> but can be changed by setting the <code>MFEPSP</code> environment variable to the new filename. Contributed by Mathias Herberts.
<code>hp2627</code>	(<code>--enable-hp2627win</code>) HP2627a color graphics terminals.
<code>mftalk</code>	(<code>--enable-mftalkwin</code>) Generic window server (see <code>web2c/window/mftalk.c</code>). ■
<code>next</code>	(<code>--enable-next</code>) NeXT window system. This requires a separate program, called <code>DrawingServant</code> , available separately. See the <code>web2c/window/next.c</code> .
<code>regis</code>	(<code>--enable-regiswin</code>) Regis terminals.
<code>sun</code>	(<code>--enable-suntoolswin</code>) The old Suntools (not any flavor of X) window system. (You can get the even older SunWindows <code>gfx</code> system by using <code>sun-gfx.c</code> .)
<code>tek</code>	(<code>--enable-tektronixwin</code>) Tektronix terminals.
<code>uniterm</code>	(<code>--enable-unitermwin</code>) Uniterm, Simon Poole's emulator of a smart Tektronix 4014 terminal. This may work with regular Tektronix terminals as well; it's faster than the driver <code>--enable-tektronixwin</code> selects.
<code>xterm</code>	<code>--with-x</code> The X window system (version 11).

There are two variants of the X11 support, one that works with the Xt toolkit, and another that works directly with Xlib. The Xt support is more efficient and has more functionality, so it is the default. If you must use the Xlib support, use `configure --with-x --with-kf-x-toolkit=no`.

Specify `--disable-mf-nowin` in order not to build a separate non-windows-capable Metafont executable `mf-nowin` (or `mf-nowin.exe`).

You cannot specify any of the usual X options (e.g., `-geometry`) on the Metafont command line, but you can specify X resources in your `~/.Xdefaults` or `~/.Xresources` file. The class name is `Metafont`. If you're using the Xt support, all the usual X toolkit resources are supported. If you're using the Xlib support, only the `geometry` resource is supported.

You specify the X display to which Metafont connects in the `DISPLAY` environment variable, as usual.

Writing support for a new device is straightforward. Aside from defining the basic drawing routines that Metafont uses (see `mf.web`), you only have to add another entry to

the tables on the last page of `web2c/lib/texmfmp.c`. Or you can write an independent program and use `Mftalk` (see `web2c/window/mftalk.c`).

6.5 GFtoDVI: Character proofs of fonts

GFtoDVI makes *proof sheets* from a GF bitmap file as output by, for example, Metafont (see Chapter 6 [Metafont], page 27). This is an indispensable aid for font designers or Metafont hackers. Synopsis:

```
gftodvi [option]... gfname[.gf]
```

The font *gfname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to `-1` before running the program.

The suffix `.gf` is supplied if not already present. This suffix is not an extension, no `.` precedes it; for instance, `cmr10.600gf`.

The output filename is the basename of *gfname* extended with `.dvi`, e.g., `gftodvi /wherever/foo.600gf` creates `./foo.dvi`.

The characters from *gfname* appear one per page in the DVI output, with labels, titles, and annotations, as specified in Appendix H (Hardcopy Proofs) of *The Metafontbook*.

GFtoDVI uses several fonts besides *gfname* itself:

- *gray font* (default `gray`): for the pixels that actually make up the character. Simply using black is not right, since then labels, key points, and other information could not be shown.
- *title font* (default `cmr8`): for the header information at the top of each output page.
- *label font* (default `cmtt10`): for the labels on key points of the figure.
- *slant font* (no default): for diagonal lines, which are otherwise simulated using horizontal and vertical rules.

To change the default fonts, you must use `special` commands in your Metafont source file, typically via commands like `slantfont slantlj4`. There is no default slant font since no one printer is suitable as a default. You can make your own by copying one of the existing files, such as `.../fonts/source/public/misc/slantlj4.mf` and then running `mf` on it.

For testing purposes, you may it useful to run `mf-nowin rtest` (hit RETURN when it stops) to get a `gf` file of a thorn glyph. Or use `mf` instead of `mf-nowin` to have the glyph(s) displayed on the screen. After that, `gftodvi rtest.2602gf` should produce `rtest.dvi`, which you process as usual.

The program accepts the following option, as well as the standard `-verbose`, `-help`, and `-version` (see Section 3.2 [Common options], page 7):

```
'-overflow-label-offset=points'
```

Typeset the so-called overflow labels, if any, *points* \TeX points from the right edge of the character bounding box. The default is a little over two inches (ten million scaled points, to be precise). Overflow equations are used to locate coordinates when their actual position is too crowded with other information.

6.6 MFT: Prettyprinting Metafont source

MFT translates a Metafont program into a T_EX document suitable for typesetting, with the aid of T_EX macros defined in the file `mftmac.tex`. Synopsis:

```
mft [option]... mfname[.mf]
```

MFT searches the usual places for *mfname* (see Section “Supported file formats” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program. The output goes to the basename of *mfname* extended with `.tex`, e.g., ‘`mft /wherever/foo.mf`’ creates `./foo.tex`.

Line breaks in the input are carried over into the output; moreover, blank spaces at the beginning of a line are converted to quads of indentation in the output. Thus, you have full control over the indentation and line breaks. Each line of input is translated independently of the others.

Further control is allowed via Metafont comments:

- Metafont comments following a single ‘%’ should be valid T_EX input. But Metafont material can be included within vertical bars in a comment; this will be translated by MFT as if it were regular Metafont code. For example, a comment like ‘% |x2r| is the tip of the bowl’ will be translated into the T_EX ‘% \$x_{2r}\$ is the ...’, i.e., the ‘x2r’ is treated as an identifier.
- ‘%%’ indicates that the remainder of an input line should be copied verbatim to the output. This is typically used to introduce additional T_EX material at the beginning or an MFT job, e.g. code to modify the standard layout or the formatting macros defined in `mftmac.tex`, or to add a line saying ‘%%\bye’ at the end of the job. (MFT doesn’t add this automatically in order to allow processing several files produces by MFT in the same T_EX job.)
- ‘%% token1 other-tokens’ introduces a change in MFT’s formatting rules; all the *other-tokens* will henceforth be translated according to the current conventions for *token1*. The tokens must be symbolic (i.e., not numeric or string tokens). For example, the input line

```
%% addto fill draw filldraw
```

says to format the ‘fill’, ‘draw’, and ‘filldraw’ operations of plain Metafont just like the primitive token ‘addto’, i.e., in boldface type. Without such reformatting commands, MFT would treat ‘fill’ like an ordinary tag or variable name. In fact, you need a ‘%%’ command even to get parentheses to act like delimiters.

- ‘%%’ introduces an MFT comment, i.e., MFT ignores the remainder of such a line.
- Five or more ‘%’ signs should not be used.

(The above description was edited from `mft.web`, written by D.E. Knuth.)

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 7):

```
‘-change=chfile[.ch]’
```

Apply the change file *chfile* as with Tangle and Weave (see Chapter 9 [WEB], page 39).

`'-style=mftfile[.mft]'`

Read *mftfile* before anything else; a MFT style file typically contains only MFT directives as described above. The default style file is named `plain.mft`, which defines this properly for programs using plain Metafont. The MFT files is searched along the `MFTINPUTS` path; see Section “Supported file formats” in *Kpathsea*.

Other examples of MFT style files are `cmbase.mft`, which defines formatting rules for the macros defined in `cm.base`, and `e.mft`, which was used in the production of Knuth’s Volume E, *Computer Modern Typefaces*.

Using an appropriate MFT style file, it is also possible to configure MFT for typesetting MetaPost sources. However, MFT does not search the usual places for MetaPost input files.

If you use eight-bit characters in the input file, they are passed on verbatim to the $\text{T}_{\text{E}}\text{X}$ output file; it is up to you to configure $\text{T}_{\text{E}}\text{X}$ to print these properly.

7 MetaPost: Generating PostScript

MetaPost is a picture-drawing language similar to Metafont (see Chapter 6 [Metafont], page 27), but instead of outputting bitmaps in a “font”, it outputs PostScript commands. It’s primarily intended for creating technical illustrations, but can also be used to create PostScript or OpenType fonts (<https://ctan.org/pkg/metatype1>).

MetaPost also provides for arbitrary integration of text and graphics in a natural way, using any typesetter (T_EX and Troff are both supported) and a number of other subsidiary programs, described below.

7.1 mpost invocation

MetaPost (installed as `mpost`) reads a series of pictures specified in the MetaPost programming language, and outputs corresponding PostScript code. This section merely describes the options available in the Web2c implementation. For a complete description of the MetaPost language, see AT&T technical report CSTR-162, generally available in `texmf/doc/metapost/`, where `texmf` is the root of T_EX directory structure. The MetaPost home page: <https://tug.org/metapost>.

Also, a standard MetaPost package for drawing graphs is documented in AT&T technical report CSTR-164, available as the file `mpgraph.ps`, generally stored alongside `mpman.ps`.

MetaPost processes its command line and determines its memory dump (`mem`) file in a way analogous to Metafont and T_EX (see Section 5.1 [tex invocation], page 17, and see Section 4.3 [Memory dumps], page 12). Synopses:

```
mpost [option]... [mpname[.mp]] [mp-commands]
mpost [option]... \first-line
mpost [option]... &mem args
```

MetaPost searches the usual places for the main input file `mpname` (see Section “Supported file formats” in *Kpathsea*), extending `mpname` with `.mp` if necessary. To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

MetaPost writes its PostScript output to a series of files `basempname.nnn` (or perhaps `basempname.ps`, very occasionally `basempname.tfm`), where `nnn` are the figure numbers specified in the input, typically to the `beginfig` macro, and `basempname` is the basename of `mpname`, or ‘`mpout`’ if no input file was specified. MetaPost uses the ‘`.ps`’ extension when the figure number is out of range, e.g., if you say `beginfig(-1)`.

You can use the output files as figures in a T_EX document just as with any other PostScript figures. For example, with this T_EX command:

```
\special{psfile="filename"}
```

or by using `epsf.tex` (see Section “EPSF macros” in *Dvips*).

The MetaPost construct

```
btex ... tex-input ... etex
```

generates a MetaPost picture expression corresponding to `tex-input`.

The construct

```
verbatimtex ... tex-input ... etex
```

simply passes the *tex-input* through to T_EX. For example, if you are using L^AT_EX, your MetaPost input file must start with a `verbatimtex` block that gives the necessary `\documentclass` (or `\documentstyle`) `\begin{document}` command. You will also need to set the environment variable `TEX` to `'latex'`.

tex-input need not be specifically T_EX input; it could also be Troff. In that case, you will need the `'-m pictures'` Troff macro package (unfortunately absent from many Troff implementations), or an equivalent such as the `'-m pspic'` macros from GNU groff described in `grops(1)`.

Naturally, you must use fonts that are supported by the typesetter; specifically, you'll probably want to use standard PostScript fonts with Troff. And only the T_EX system understands Computer Modern or other Metafont fonts; you can also use PostScript fonts with T_EX, of course.

MetaPost-generated PostScript figures which do use Computer Modern fonts for labels cannot be directly previewed or printed. Instead, you must include them in a T_EX document and run the resulting DVI file through Dvips to arrange for the downloading of the required fonts (see Section "Fonts in figures" in *Dvips*). To help with this, the MetaPost distribution provides a small T_EX file `mproof.tex` which is typically called as:

```
tex mproof mp-output-files... ; dvips mproof -o
```

The resulting file `mproof.ps` can then be printed or previewed.

To generate EPSF files, set the internal MetaPost variable `prologues` positive. To make the output files self-contained, use only standard PostScript fonts. MetaPost reads the same `psfonts.map` file as Dvips, to determine PostScript fonts that need to be downloaded (see Section "psfonts.map" in *Dvips*).

It is possible for pdfT_EX to read MetaPost output directly; this is in contrast to general EPSF files, which have to be converted for use with PDF output. The easiest way is to name the MetaPost output files with the `.mps` extension. Then the L^AT_EX `\includegraphics` command, for example, will be able to read them, even when outputting PDF.

MetaPost can write output files, via the `write` primitive; this opens a security hole. See Section 5.1 [tex invocation], page 17.

The program accepts the following options, as well as the standard `'-help'` and `'-version'` (see Section 3.2 [Common options], page 7):

```
'-[no]-file-line-error'
'-fmt=fmtname'
'-halt-on-error'
'-ini'
'-interaction=string'
'-jobname=string'
'-kpathsea-debug=number'
'-[no]parse-first-line'
'-output-directory'
'-progname=string'
'-recorder'
'-translate-file=tcxfile'
```

`'-8bit'` These options are common to T_EX, Metafont, and MetaPost. See Section 3.2 [Common options], page 7.

‘-T’

‘-troff’ Set the `prologues` internal variable to 1.

‘-tex=*texprogram*’

When this option is given, the program *texprogram* is used to typeset the labels.

7.2 Initial MetaPost

As of MetaPost 1.504 (T_EX Live 2011), MetaPost no longer dumps `.mem` files (see Section 4.3 [Memory dumps], page 12) and does not distinguish virgin and initial forms (see Section 4.2 [Initial and virgin], page 12). Instead, the “initial” file name is read in its source form—that is, `mpost.mp` when the program is invoked as `mpost`.

For a list of options and other information, see Section 7.1 [mpost invocation], page 34.

MetaPost provides a format with all the features of plain Metafont, called `mfplain`. You can use that in the same way; just run `mfplain` instead of `mpost`. This lets you directly process Metafont source files with MetaPost, producing character proofs (one file for each character) similar to those produced with Metafont in proof mode and GFToDVI (see Section 6.5 [gftodvi invocation], page 31).

7.3 DVItOMP: DVI to MPX conversion

DVItOMP converts DVI files into low-level MetaPost commands in a so-called MPX file. Synopsis:

```
dvitomp dvifile [.dvi] [mpxfile [.mpx]]
```

If *mpxfile* is not specified, the output goes to the basename of *dvifile* extended with `.mpx`, e.g., `dvitomp /wherever/foo.dvi` creates `./foo.mpx`.

DVItOMP supports Dvips-style color specials, such as ‘`color push name`’ and ‘`color pop`’, outputting them as `withcolor` MetaPost commands.

The only options are ‘`-help`’ and ‘`-version`’ (see Section 3.2 [Common options], page 7).

8 Bib_TE_X: Bibliographies

Bib_TE_X automates much of the job of typesetting bibliographies, and makes bibliography entries reusable in many different contexts.

8.1 Bib_TE_X invocation

Bib_TE_X creates a printable bibliography (`.bbl`) file from references in a `.aux` file, generally written by $\text{T}_{\text{E}}\text{X}$ or $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$. The `.bbl` file is then incorporated on a subsequent run. The basic bibliographic information comes from `.bib` files, and a Bib_TE_X style (`.bst`) file controls the precise contents of the `.bbl` file. Synopsis:

```
bibtex [option]... auxfile[.aux]
```

The output goes to the basename of `auxfile` extended with `.bbl`; for example, `'bibtex /wherever/foo.aux'` creates `./foo.bbl`. Bib_TE_X also writes a log file to the basename of `auxfile` extended with `.blg`.

The names of the `.bib` and `.bst` files are specified in the `.aux` file as well, via the `\bibliography` and `\bibliographystyle` (La) $\text{T}_{\text{E}}\text{X}$ macros. Bib_TE_X searches for `.bib` files using the `BIBINPUTS` and `TEXBIB` paths, and for `.bst` files using `BSTINPUTS` (see Section “Supported file formats” in *Kpathsea*). It does no path searching for `.aux` files.

The program accepts the following options, as well as the standard `-help` and `-version` (see Section 3.2 [Common options], page 7):

`-terse` Suppress the program banner and progress reports normally output.

`-min-crossrefs=n`

If at least n (2 by default) bibliography entries refer to another entry e via their `crossref` field, include e in the `.bbl` file, even if it was not explicitly referenced in the `.aux` file. For example, e might be a conference proceedings as a whole, with the cross-referencing entries being individual articles published in the proceedings.

If you want to avoid these automatic inclusions altogether, make n a sufficiently large number, and be sure to remove any previous `.aux` and `.bbl` files. Otherwise the option may appear to have no effect, since Bib_TE_X will have added the citation for e to the `.aux`, and nothing will remove it.

See also:

`btxdoc.tex`

Basic $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ able documentation for general Bib_TE_X users.

`btXHak.tex`

$\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ able documentation for style designers.

`btxdoc.bib`

Bib_TE_X database file for the two above documents.

`xampl.bib`

Example database file with all the standard entry types.

`ftp://ftp.math.utah.edu/pub/tex/bib/`

A very large `.bib` and `.bst` collection, including references for all the standard $\text{T}_{\text{E}}\text{X}$ books and a complete bibliography for TUGboat.

8.2 Basic BibTeX style files

Here are descriptions of the four standard and four semi-standard basic BibTeX styles. *CTAN:/biblio/bibtex* contains these and many more (for CTAN info, see Section “unix-tex.ftp” in *Kpathsea*).

<code>plain</code>	Sorts entries alphabetically, with numeric labels. Generally formatted according to van Leunen’s <i>A Handbook for Scholars</i> . The other style files listed here are based on <code>plain</code> .
<code>abbrv</code>	First names, month names, and journal names are abbreviated.
<code>acm</code>	Names are printed in small caps.
<code>alpha</code>	Alphanumeric labels, e.g., ‘Knu66’.
<code>apalike</code>	No labels at all; instead, the year appears in parentheses after the author. Use this in conjunction with <code>apalike.tex</code> (plain TeX) or <code>apalike.sty</code> (LaTeX), which also changes the citations in the text to be ‘(author, year)’.
<code>ieeetr</code>	Numeric labels, entries in citation order, IEEE abbreviations, article titles in quotes.
<code>siam</code>	Numeric labels, alphabetic order, <i>Math. Reviews</i> abbreviations, names in small caps.
<code>unsrt</code>	Lists entries in citation order, i.e., unsorted.
<code>btbst.doc</code>	The template file and documentation for the standard styles.

9 WEB: Literate programming

WEB languages allow you to write a single source file that can produce both a compilable program and a well-formatted document describing the program in as much detail as you wish to prepare. Writing in this kind of dual-purpose language is called *literate programming*. (The Usenet newsgroup `comp.programming.literate` is devoted to this subject.)

WEB-like languages have been implemented with many pairs of base languages: Cweb provides C and Troff (see Appendix B [References], page 56); CWEB provides C and T_EX (`CTAN:/web/c_cpp/cweb`); Spiderweb provides C, C++, Awk, Ada, many others, and T_EX (`CTAN:/web/spiderweb`); and, of course, the original WEB provides Pascal and T_EX, the implementation languages for the original T_EX, Metafont, MetaPost, and related programs to come from the T_EX project at Stanford.

The original WEB language is documented in the file `webman.tex`, which is included in the `ftp://ftp.tug.org/tex/lib.tar.gz` archive (and available in many other places, of course).

9.1 Tangle: Translate WEB to Pascal

Tangle creates a compilable Pascal program from a WEB source file (see Chapter 9 [WEB], page 39). Synopsis:

```
tangle [option]... webfile[.web] [changefile[.ch]]
```

The Pascal output is written to the basename of *webfile* extended with `.p`; for example, `'tangle /wherever/foo.web'` creates `./foo.p`. Tangle applies *changefile* to *webfile* before writing the output; by default, there is no change file.

If the program makes use of the WEB string facility, Tangle writes the string pool to the basename of *webfile* extended with `.pool`.

The Pascal output is packed into lines of 72 characters or less, with the only concession to readability being the termination of lines at semicolons when this can be done conveniently.

The program accepts the following options, as well as the standard `--help` and `--version` (see Section 3.2 [Common options], page 7):

`'-length=number'`

The number of characters that are considered significant in an identifier. Whether underline characters are counted depends on the `'-underline'` option. The default value is 32, the original tangle used 7, but this proved too restrictive for use by Web2c.

`'-lowercase'`

`'-mixedcase'`

`'-uppercase'`

These options specify the case of identifiers in the output of tangle. If `'-uppercase'` (`'-lowercase'`) is specified, tangle will convert all identifiers to uppercase (lowercase). The default is `'-mixedcase'`, which specifies that the case will not be changed.

`'-underline'`

When this option is given, tangle does not strip underline characters from identifiers.

‘-loose’
‘-strict’ These options specify how strict tangle must be when checking identifiers for equality. The default is ‘-loose’, which means that tangle will follow the rules set by the case-smashing and underline options above. If ‘-strict’ is set, then identifiers will always be stripped of underlines and converted to uppercase before checking whether they collide.

9.2 Weave: Translate WEB to T_EX

Weave creates a T_EX document from a WEB source file (see Chapter 9 [WEB], page 39), assuming various macros defined in `webmac.tex`. It takes care of typographic details such as page layout, indentation, and italicizing identifiers. It also automatically gathers and outputs extensive cross-reference information. Synopsis:

```
weave [option]... webfile[.web] [changefile[.ch]]
```

The output is to the basename of `webfile` extended with ‘.tex’; for example, ‘weave /wherever/foo.web’ creates `./foo.tex`. Weave applies `changefile` to `webfile` before writing the output; by default, there is no change file.

The program accepts the following option, as well as the standard ‘-verbose’, ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 7):

‘-x’ Omit the cross-reference information: the index, the list of WEB module names, and the table of contents (an empty `CONTENTS.tex` file will still be written when the Weave output file is processed by T_EX using the default `webmac.tex`, though).

Conventionally, WEB programmers should define the T_EX `\title` macro at the beginning of the source file. Also, to get output of only changed modules, one can say `\let\maybe=\iffalse` (usually as the first change in the change file).

9.3 Pooltype: Display WEB pool files

Pooltype shows the so-called *string number* of each string in a WEB pool file (see Chapter 9 [WEB], page 39), as output by Tangle (see Section 9.1 [tangle invocation], page 39), including the first 256 strings corresponding to the possible input characters. Pooltype primarily serves as an example of WEB conventions to implementors of the T_EX system. Synopsis:

```
pooltype [option]... poolfile[.pool]
```

No path searching is done for `poolfile`. Output is to standard output.

The only options are ‘--help’ and ‘--version’ (see Section 3.2 [Common options], page 7).

As an example of the output, here is the (edited) output for `tex.pool`:

```
0: "^^@"
1: "^^A"
...
255: "^^ff"
256: "pool size"
...
1314: "Using character substitution: "
```

(23617 characters in all.)

In Metafont and MetaPost, the first 256 characters are actually represented as single bytes (i.e., themselves), not in the ‘^^’ notation. Consider Pooltype as showing the results after conversion for output.

10 DVI utilities

\TeX outputs a file in *DVI* (DeVice Independent) format as a compact representation of the original document. DVI files can be translated to meet the requirements of a real physical device, such as PostScript printers (see Section “Introduction” in *Dvips*), PCL printers (see `dvilj(1)`), and X displays (see `xdvi(1)`). In fact, DVI translators are available for virtually all common devices: see *CTAN:/dviware* (for CTAN info, see Section “unixtex.ftp” in *Kpathsea*).

For the precise definition of the DVI file format, see (for example) the source file `web2c/dvitype.web`.

The DVI-processing programs in the Web2c distribution are not device drivers; they perform generic utility functions.

10.1 DVICopy: Canonicalize virtual font references

DVICopy reads a DVI file, expands any references to virtual fonts (see Section “Virtual fonts” in *Dvips*) to base fonts, and writes the resulting DVI file. Thus you can use virtual fonts even if your DVI processor does not support them, by passing the documents through DVICopy first. Synopsis:

```
dvicopy [option]... [indvi[.dvi] [outdvi[.dvi]]]
```

DVICopy reads standard input if *indvi* is not specified, and writes standard output if *outdvi* is not specified.

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 7):

‘-magnification=*integer*’

Override existing magnification in *indvi* with *integer*; 1000 specifies no magnification. This is equivalent to setting \TeX ’s `\mag` parameter.

‘-max-pages=*n*’

Process *n* pages; default is one million.

‘-page-start=*page-spec*’

Start at the first page matching *page-spec*, which is one or more (signed) integers separated by periods, corresponding to \TeX ’s `\count0...9` parameters at `\shipout` time; ‘*’ matches anything. Examples: ‘3’, ‘1.*.-4’.

10.2 DVIType: Plain text transliteration of DVI files

DVIType translates a DeVice Independent (DVI) file (as output by \TeX , for example) to a plain text file that humans can read. It also serves as a DVI-validating program, i.e., if DVIType can read a file, it’s correct. Synopsis:

```
dvitype [option]... dvifile[.dvi]
```

DVIType does not read any bitmap files, but it does read TFM files for fonts referenced in *dvifile*. The usual places are searched (see Section “Supported file formats” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

Output goes to standard output.

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 7):

‘-dpi=*real*’

Do pixel movement calculations at *real* pixels per inch; default 300.0.

‘-magnification=*integer*’

Override existing magnification in *indvi* with *integer*; 1000 specifies no magnification. This is equivalent to setting T_EX’s \mag parameter.

‘-max-pages=*n*’

Process *n* pages; default is one million.

‘-output-level=*n*’

Verbosity level of output, from 0 to 4 (default 4):

- 0: Global document information only.
- 1: Most DVI commands included, and typeset characters summarized.
- 2: Character and movement commands explicitly included.
- 3: DVI stack and current position calculations included.
- 4: Same information as level 3, but DVIt_ype does random positioning in the file, reading the DVI postamble first.

‘-page-start=*page-spec*’

Start at the first page matching *page-spec*, which is one or more (signed) integers separated by periods, corresponding to T_EX’s \count0...9 parameters at \shipout time; ‘*’ matches anything. Examples: ‘1’, ‘5.*.-9’.

‘-show-opcodes’

Show numeric opcode values (in decimal) for DVI commands, in braces after the command name. This can help in debugging DVI utilities. We use decimal because in the DVI format documentation (in *dvitype.web*, among others) the opcodes are shown in decimal.

10.2.1 DVIt_ype output example

As an example of the output from DVIt_ype (see section above), here is its (abridged) translation of the *story.dvi* resulting from running the example in *The T_EXbook*, with ‘-output-level=4’ and ‘-show-opcodes’ on.

```
...
Options selected:
  Starting page = *
  Maximum number of pages = 1000000
  Output level = 4 (the works)
  Resolution = 300.00000000 pixels per inch
numerator/denominator=25400000/473628672
magnification=1000;      0.00006334 pixels per DVI unit
' TeX output 1992.05.17:0844'
Postamble starts at byte 564.
```

```

maxv=43725786, maxh=30785863, maxstackdepth=3, totalpages=1
Font 33: cmsl10---loaded at size 655360 DVI units
Font 23: cmbx10---loaded at size 655360 DVI units
Font 0: cmr10---loaded at size 655360 DVI units

42: beginning of page 1
87: push {141}
level 0: (h=0,v=0,w=0,x=0,y=0,z=0,hh=0,vv=0)
88: down3 -917504 {159} v:=0-917504=-917504, vv:=-58
92: pop {142}
...
104: putrule {137} height 26214, width 30785863 (2x1950 pixels)
113: down3 5185936 {159} v:=655360+5185936=5841296, vv:=370
117: push {141}
level 1: (h=0,v=5841296,w=0,x=0,y=0,z=0,hh=0,vv=370)
118: right4 12265425 {146} h:=0+12265425=12265425, hh:=777
[ ]
123: fntdef1 23 {243}: cmbx10
145: fntnum23 {194} current font is cmbx10
146: setchar65 h:=12265425+569796=12835221, hh:=813
147: w3 251220 {150} h:=12835221+251220=13086441, hh:=829
151: setchar83 h:=13086441+418700=13505141, hh:=856
...
164: setchar82 h:=17448202+565245=18013447, hh:=1142
165: x0 -62805 {152} h:=18013447-62805=17950642, hh:=1138
166: setchar89 h:=17950642+569796=18520438, hh:=1174
[A SHORT STORY]
167: pop {142}
level 1: (h=0,v=5841296,w=0,x=0,y=0,z=0,hh=0,vv=370)
...
550: pop {142}
level 0: (h=0,v=42152922,w=0,x=0,y=0,z=0,hh=0,vv=2670)
551: down3 1572864 {159} v:=42152922+1572864=43725786, vv:=2770
555: push {141}
level 0: (h=0,v=43725786,w=0,x=0,y=0,z=0,hh=0,vv=2770)
556: right4 15229091 {146} h:=0+15229091=15229091, hh:=965
561: setchar49 h:=15229091+327681=15556772, hh:=986
[ 1]
562: pop {142}
level 0: (h=0,v=43725786,w=0,x=0,y=0,z=0,hh=0,vv=2770)
563: eop {140}

```

Explanation:

- The DVItyp options are recorded at the beginning, followed by global information about the document, including fonts used.
- Each DVI command is preceded by its byte position in the file ('42:', '87:', ...),

and (because of the `'-show-opcodes'`) followed by its decimal opcode value in braces (`'{141}'`, `'{142}'`, ...).

- The `'level'` lines record information about the DVI stack; `'h'` and `'v'` define the current position in DVI units, while `'hh'` and `'vv'` are the same in pixels.
- Text sequences are summarized in brackets, as in `'[A SHORT STORY]'` and the `'[1]'`.

11 Font utilities

The Web2c programs described here convert between various T_EX-related font formats; the first section below briefly describes the formats. GFtoPK is the only one that is routinely used, as Metafont outputs GF format, but it's most efficient for device drivers to use PK.

The precise definitions of the PK, GF, TFM, PL, VF, and VPL formats mentioned below are in the source files that read them; `pktype.web`, `gftype.web`, `tftopl.web`, etc.

11.1 Font file formats

For another perspective on this, see Section “Font concepts” in *Dvips*.

Font files come in several varieties, with suffixes like:

`.tfm` `.*pk` `.*gf` `.*pxl` (obsolete) `.pl` `.mf` `.vf` `.vpl`

Each represents a file format.

A TFM (T_EX font metric) file is a compact binary file that contains information about each character in a font, about combinations of characters within that font, and about the font as a whole. The font metric information contained in TFM files is device-independent units is used by T_EX to do typesetting. Unlike the bitmap (raster) fonts described below, TFM font files contain no information about the shapes of characters. They describe rectangular areas and combinations thereof, but not what will eventually be printed in those areas.

Since T_EX does scaling calculations, one TFM file serves for all magnifications of a given typeface. On the other hand, the best printed results are obtained when magnified (or reduced fonts) are not produced geometrically (as done by PostScript, for example) but rather optically, with each size a separate design (as done with Computer Modern and the EC fonts, for example); then a separate TFM file is needed for each size.

At any rate, T_EX produces a DVI (DeVice Independent) file from your source document. In order to print DVI files on real devices, you need font files defining digitized character shapes and other data. Then previewers and printer-driver programs can translate your DVI files into something usable by your monitor or printer. Bitmap fonts come with suffixes such as ‘.600pk’ or ‘.600gf’ or ‘.3000pxl’, where the ‘600’ is the horizontal dots-per-inch resolution at which the font was produced, and the ‘pk’ or ‘gf’ or ‘pxl’ indicates the font format. Outline fonts in PostScript Type 1 format have suffixes such as ‘.pfa’ or ‘.pfb’.

Fonts in pk (packed) format are in the tightly packed raster format that is pretty much the standard today. They take up less space than fonts in the gf (generic font) format that Metafont generates, and far less space than fonts in pxl format. Fonts in pxl format take up gross amounts of disk space and permit only 128 characters. They are obsolete.

Font files with the ‘.pl’ (property list) suffix are the plain text (human-readable) analog of the binary ‘.tfm’ files. The TFtoPL and PLtoTF programs convert between the two formats (see Section 11.6 [tftopl invocation], page 51, and Section 11.7 [pltotf invocation], page 53).

Font files with the ‘.mf’ suffix are in Metafont source format. These are the files used by Metafont to generate rastered fonts for specific typefaces at specific magnifications for the specific resolution and type of mapping used by your device.

The suffix ‘.vf’ identifies “virtual font” files, for which ‘.vpl’ is the human-readable analog. See Section 11.8 [vftovp invocation], page 53, and Section 11.9 [vptovf invocation], page 54. For further discussion of virtual fonts, see *CTAN:/doc/virtual-fonts.knuth*, *CTAN:/help/virtualfonts.txt*, and Section “Virtual fonts” in *Dvips*.

(This section is based on documentation in the original Unix T_EX distribution by Pierre MacKay and Elizabeth Tachikawa.)

11.2 GFtoPK: Generic to packed font conversion

GFtoPK converts a generic font (GF) file output by, for example, Metafont (see Section 6.1 [mf invocation], page 27) to a packed font (PK) file. PK files are considerably smaller than the corresponding gf files, so they are generally the bitmap font format of choice. Some DVI-processing programs, notably Dvips, only support PK files and not GF files. Synopsis:

```
gftopk [option]... gfname.dpi[gf] [pkfile]
```

The font *gfname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

The suffix ‘*gf*’ is supplied if not already present. This suffix is not an extension; no ‘.’ precedes it: for instance, `cmr10.600gf`.

If *pkfile* is not specified, the output is written to the basename of ‘*gfname.dpipk*’, e.g., ‘`gftopk /wherever/cmr10.600gf`’ creates `./cmr10.600pk`.

The only options are ‘--verbose’, ‘--help’, and ‘--version’ (see Section 3.2 [Common options], page 7).

11.3 PKtoGF: Packed to generic font conversion

PKtoGF converts a packed font (PK) file to a generic font (GF) file. Since PK format is much more compact than GF format, the most likely reason to do this is to run GFtype (see Section 11.5 [gftype invocation], page 49) on the result, so you can see the bitmap images. Also, a few old utility programs do not support PK format. Synopsis:

```
pktoGF [option]... pkname.dpi[pk] [gffile]
```

The font *pkname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

The suffix ‘*pk*’ is supplied if not already present. This suffix is not an extension; no ‘.’ precedes it: for instance, `cmr10.600pk`.

If *gffile* is not specified, the output is written to the basename of ‘*pkname.dpigf*’, e.g., ‘`pktoGF /wherever/cmr10.600pk`’ creates `./cmr10.600gf`.

The only options are ‘--verbose’, ‘--help’, and ‘--version’ (see Section 3.2 [Common options], page 7).

11.4 PKtype: Plain text transliteration of packed fonts

PKtype translates a packed font (PK) bitmap file (as output by GFtoPK, for example) to a plain text file that humans can read. It also serves as a PK-validating program, i.e., if PKtype can read a file, it’s correct. Synopsis:

```
pktype pkname.dpi [pk]
```

The font *pkname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

The suffix ‘pk’ is supplied if not already present. This suffix is not an extension; no ‘.’ precedes it: for instance, `cmr10.600pk`.

The translation is written to standard output.

The only options are ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 7).

As an example of the output, here is the (abridged) translation of the letter ‘K’ in ‘cmr10’, as rendered at 600dpi with the mode ‘ljfour’ from `modes.mf` (available from `ftp://ftp.tug.org/tex/modes.mf`).

```
955:  Flag byte = 184  Character = 75  Packet length = 174
      Dynamic packing variable = 11
      TFM width = 815562  dx = 4259840
      Height = 57  Width = 57  X-offset = -3  Y-offset = 56
      [2]23(16)17(8)9(25)11(13)7(27)7(16)7(28)4(18)7(28)2(20)7(27)...
      ...
      (14)9(24)12(5) [2]23(13)21
```

Explanation:

‘955’ The byte position in the file where this character starts.

‘Flag byte’

‘Dynamic packing variable’

Related to the packing for this character; see the source code.

‘Character’

The character code, in decimal.

‘Packet length’

The total length of this character definition, in bytes.

‘TFM width’

The device-independent (TFM) width of this character. It is 2^{24} times the ratio of the true width to the font’s design size.

‘dx’

The device-dependent width, in *scaled pixels*, i.e., units of horizontal pixels times 2^{16} .

‘Height’

‘Width’ The bitmap height and width, in pixels.

‘X-offset’

‘Y-offset’

Horizontal and vertical offset from the upper left pixel to the reference (origin) pixel for this character, in pixels (right and down are positive). The *reference pixel* is the pixel that occupies the unit square in Metafont; the Metafont reference point is the lower left hand corner of this pixel. Put another way, the x-offset is the negative of the left side bearing; the right side bearing is the horizontal escapement minus the bitmap width plus the x-offset.

‘[2]23(16)...’

Finally, run lengths of black pixels alternate with parenthesized run lengths of white pixels, and brackets indicate a repeated row.

11.5 Gftype: Plain text transliteration of generic fonts

Gftype translates a generic font (GF) bitmap file (as output by Metafont, for example) to a plain text file that humans can read. It also serves as a GF-validating program, i.e., if Gftype can read a file, it’s correct. Synopsis:

```
gftype [option]... gfname.dpi[gf]
```

The font *gfname* is searched for in the usual places (see Section “Glyph lookup” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program.

The suffix ‘*gf*’ is supplied if not already present. This suffix is not an extension; no ‘.’ precedes it: for instance, `cmr10.600gf`.

The translation is written to standard output.

The program accepts the following options, as well as the standard ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 7):

‘-images’ Show the characters’ bitmaps using asterisks and spaces.

‘-mnemonics’

Translate all commands in the GF file.

As an example of the output, here is the (abridged) translation of the letter ‘K’ in ‘*cmr10*’, as rendered at 600 dpi with the mode ‘*ljfour*’ from *modes.mf* (available from <ftp://ftp.tug.org/tex/modes.mf>), with both ‘-mnemonics’ and ‘-images’ enabled.

Gftype outputs the information about a character in two places: a main definition and a one-line summary at the end. We show both. Here is the main definition:

```
2033: beginning of char 75: 3<=m<=60 0<=n<=56
      (initially n=56) paint(0)24(12)20
2043: newrow 0 (n=55) paint 24(12)20
2047: newrow 0 (n=54) paint 24(12)20
2051: newrow 0 (n=53) paint 24(12)20
2055: newrow 7 (n=52) paint 10(21)13
2059: newrow 8 (n=51) paint 8(23)9
...
2249: newrow 8 (n=5) paint 8(23)11
2253: newrow 7 (n=4) paint 10(22)12
2257: newrow 0 (n=3) paint 24(11)22
2261: newrow 0 (n=2) paint 24(11)22
2265: newrow 0 (n=1) paint 24(11)22
2269: newrow 0 (n=0) paint 24(11)22
2273: eoc
```


11.6 TFtoPL: T_EX font metric to property list conversion

TFtoPL translates a T_EX font metric (TFM, see Section “Metric files” in *Dvips*) file (as output by Metafont, for example) to *property list format* (a list of parenthesized items describing the font) that humans can edit or read. This program is mostly used by people debugging T_EX implementations, writing font utilities, etc. Synopsis:

```
tftopl [option]... tfmname[.tfm] [plfile[.pl]]
```

The font *tfmname* (extended with `.tfm` if necessary) is searched for in the usual places (see Section “Supported file formats” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to `-1` before running the program.

If *plfile* (which is extended with `.pl` if necessary) is not specified, the property list file is written to standard output. The property list file can be converted back to TFM format by the companion program TFtoPL (see the next section).

The program accepts the following option, as well as the standard `-verbose`, `-help` and `-version` (see Section 3.2 [Common options], page 7):

`-charcode-format=type`

Output character codes in the PL file according to *type*: either `octal` or `ascii`. Default is `ascii` for letters and digits, octal for all other characters. Exception: if the font’s coding scheme starts with `TeX math sy` or `TeX math ex`, all character codes are output in octal.

In `ascii` format, character codes that correspond to graphic characters, except for left and right parentheses, are output as a `C` followed by the single character: `C K`, for example. In octal format, character codes are output as the letter `O` followed by octal digits, as in `O 113` for `K`.

`octal` format is useful for symbol and other non-alphabetic fonts, where using ASCII characters for the character codes is merely confusing.

As an example of the output, here is the (abridged) property list translation of `cmr10.tfm`:

```
(FAMILY CMR)
(FACE 0 352)
(CODINGScheme TEX TEXT)
(DESIGNSIZE R 10.0)
(COMMENT DESIGNSIZE IS IN POINTS)
(COMMENT OTHER SIZES ARE MULTIPLES OF DESIGNSIZE)
(CHECKSUM 0 11374260171)
(FONTDIMEN
  (SLANT R 0.0)
  (SPACE R 0.333334)
  (STRETCH R 0.166667)
  (SHRINK R 0.111112)
  (XHEIGHT R 0.430555)
  (QUAD R 1.000003)
  (EXTRASPACE R 0.111112)
)
(LIGTABLE
```

```

...
(LABEL C f)
(LIG C i 0 14)
(LIG C f 0 13)
(LIG C l 0 15)
(KRN 0 47 R 0.077779)
(KRN 0 77 R 0.077779)
(KRN 0 41 R 0.077779)
(KRN 0 51 R 0.077779)
(KRN 0 135 R 0.077779)
(STOP)
...
)
...
(CHARACTER C f
  (CHARWD R 0.305557)
  (CHARHT R 0.694445)
  (CHARIC R 0.077779)
  (COMMENT
    (LIG C i 0 14)
    (LIG C f 0 13)
    (LIG C l 0 15)
    (KRN 0 47 R 0.077779)
    (KRN 0 77 R 0.077779)
    ...
  )
)
...

```

As you can see, the general format is a list of parenthesized *properties*, nested where necessary.

- The first few items (FAMILY, FACE, and so on) are the so-called *headerbyte* information from Metafont, giving general information about the font.
- The FONTDIMEN property defines the \TeX `\fontdimen` values.
- The LIGTABLE property defines the ligature and kerning table. LIG properties define ligatures: in the example above, an ‘f’ (in the ‘LABEL’) followed by an ‘i’ is a ligature, i.e., a typesetting program like \TeX replaces those two consecutive characters by the character at position octal ‘014 in the current font—presumably the ‘fi’ ligature. KRN properties define kerns: if an ‘f’ is followed by character octal ‘047 (an apostrophe), \TeX inserts a small amount of space between them: 0.077779 times the design size the font was loaded at (about three-quarters of a printer’s point by default in this case, or .001 inches).
- The CHARACTER property defines the dimensions of a character: its width, height, depth, and italic correction, also in design-size units, as explained in the previous item. For our example ‘f’, the depth is zero, so that property is omitted. T_FtoP_L also inserts any kerns and ligatures for this character as a comment.

11.7 PLtoTF: Property list to T_EX font metric conversion

PLtoTF translates a property list file (as output by TFtoPL, for example) to T_EX font metric (TFM, see Section “Metric files” in *Dvips*) format. It’s much easier for both programs and humans to create the (plain text) property list files and let PLtoTF take care of creating the binary TFM equivalent than to output TFM files directly. Synopsis:

```
pltotf [option]... plfile[.pl] [tfmfile[.tfm]]
```

If *tfmfile* (extended with ‘.tfm’ if necessary) is not specified, the TFM file is written to the basename of *plfile.tfm*, e.g., `pltotf /wherever/cmr10.pl` creates `./cmr10.tfm`. (Since TFM files are binary, writing to standard output by default is undesirable.)

The only options are ‘-verbose’, ‘-help’, and ‘-version’ (see Section 3.2 [Common options], page 7).

For an example of property list format, see the previous section.

11.8 VFtoVP: Virtual font to virtual property lists

VFtoVP translates a virtual font metric (VF, see Section “Virtual fonts” in *Dvips*) file and its accompanying T_EX font metric (TFM, see Section “Metric files” in *Dvips*) file (as output by VPtoVF, for example) to *virtual property list format* (a list of parenthesized items describing the virtual font) that humans can edit or read. This program is mostly used by people debugging virtual font utilities. Synopsis:

```
vftovp [option]... vfname[.vf] [tfmname[.tfm] [vpfile[.vpl]]]
```

The fonts *vfname* and *tfmname* (extended with ‘.vf’ and ‘.tfm’ if necessary) are searched for in the usual places (see Section “Supported file formats” in *Kpathsea*). To see all the relevant paths, set the environment variable `KPATHSEA_DEBUG` to ‘-1’ before running the program. If *tfmname* is not specified, *vfname* (without a trailing ‘.vf’) is used.

If *vpfile* (extended with ‘.vpl’ if necessary) is not specified, the property list file is written to standard output. The property list file can be converted back to VF and TFM format by the companion program VFtoVP (see the next section).

The program accepts the following option, as well as the standard ‘-verbose’, ‘-help’ and ‘-version’ (see Section 3.2 [Common options], page 7):

‘-charcode-format=type’

Output character codes in the PL file according to *type*: either ‘octal’ or ‘ascii’. Default is ‘ascii’ for letters and digits, octal for all other characters. Exception: if the font’s coding scheme starts with ‘T_EX math sy’ or ‘T_EX math ex’, all character codes are output in octal.

In ‘ascii’ format, character codes that correspond to graphic characters, except for left and right parentheses, are output as a ‘C’ followed by the single character: ‘C K’, for example. In octal format, character codes are output as the letter ‘O’ followed by octal digits, as in ‘O 113’ for ‘K’.

‘octal’ format is useful for symbol and other non-alphabetic fonts, where using ASCII characters for the character codes is merely confusing.

11.9 VPtoVF: Virtual property lists to virtual font

VPtoVF translates a virtual property list file (as output by VFtoVP, for example) to virtual font (VF, see Section “Virtual fonts” in *Dvips*) and T_EX font metric (TFM, see Section “Metric files” in *Dvips*) files. It’s much easier for both programs and humans to create the (plain text) property list files and let VPtoVF take care of creating the binary VF and TFM equivalents than to output them directly. Synopsis:

```
vptovf [option]... vplfile[.vpl] [vffile[.vf] [tfmfile[.tfm]]]
```

If *vffile* (extended with ‘.vf’ if necessary) is not specified, the VF output is written to the basename of ‘*vplfile.vf*’; similarly for *tfmfile*. For example, ‘`vptovf /wherever/ptmr.vpl`’ creates `./ptmr.vf` and `./ptmr.tfm`.

The only options are ‘-verbose’, ‘-help’, and ‘-version’ (see Section 3.2 [Common options], page 7).

11.10 Font utilities available elsewhere

The Web2c complement of font utilities merely implements a few basic conversions. Many other more sophisticated font utilities exist; most are in *CTAN:/fonts/utilities* (for CTAN info, see Section “unixtex.ftp” in *Kpathsea*). Here are some of the most commonly-requested items:

- AFM (Adobe font metric) to TFM conversion: see Section “Invoking afm2tfm” in *Dvips*, and *CTAN:/fonts/utilities/afm2tfm*.
- BDF (the X bitmap format) conversion: <ftp://ftp.tug.org/tex/bdf.tar.gz>.
- Creating fonts using MetaPost: MetaType1. <ftp://bop.eps.gda.pl/pub/metatype1>. This is used to create the excellent Latin Modern font family (*CTAN:/fonts/lm*), which extends Computer Modern to a vast repertoire of scripts.
- Editing of bitmap fonts: Xbfe from the GNU font utilities mentioned below; the X BDF-editing programs available from <ftp://ftp.x.org/R5contrib/xfed.tar.Z> and <ftp://ftp.x.org/R5contrib/xfedor.tar.Z>; and finally, if your fonts have only 128 characters, you can use the old `gftopxl`, `pctocho`, and `chtopx` programs from <ftp://ftp.tug.org/tex/web>.
- Editing of outline fonts: FontForge, fontforge.sourceforge.net. This is a very elaborate program with support for many outline formats (Type 1, OpenType, TrueType, ...), and many advanced font editing features.
- PK bitmaps from PostScript outline fonts: `gsftopk` from the ‘`xdvi`’ distribution. Alternatively, `ps2pk`, from *CTAN:/fonts/utilities/ps2pk*.
- PostScript Type 1 font format conversion (i.e., between PFA and PFB formats): <https://www.lcdf.org/type>.
- Tracing bitmaps to fitted outlines: Autotrace (<http://autotrace.sourceforge.net>), Potrace (<http://potrace.sourceforge.net>). For Metafont fonts, either of the two programs `mftrace` (<http://www.xs4all.nl/~hanwen/mftrace>) or `textrace` (<http://textrace.sourceforge.net>) make the job easier.
- Virtual font creation: <https://ctan.org/pkg/fontinst>.

Appendix A Legalisms

In general, each file has its own copyright notice stating the copying permissions for that file. Following is a summary.

The Stanford \TeX programs and Web2c system itself are in the public domain (<https://tug.org/texlive/copying.html>). The sources may be copied verbatim, or used as the starting point of new software under different names; however, per the wishes of the authors, they should be modified only through a `.ch` file, but this is in the nature of a development request rather than a legal requirement.

ML \TeX , pdf \TeX , Lua \TeX , Xe \TeX , and all the other derived engines have used various license terms for their additions to the base code, often the GPL (see <https://www.gnu.org/licenses/#GPL>) or (for example) the file `web2c/pdftexdir/COPYINGv2`. They also mostly make use of additional libraries with their own (compatible) terms. Please see each program's sources.

The Kpathsea library is covered by the GNU Lesser General Public License (see Section “Introduction” in *Kpathsea*). Therefore, the *binaries* resulting from a standard Web2c compilation are also covered by the LGPL; so if you (re)distribute the binaries, you must also (offer to) distribute the complete source that went into those binaries. See <https://gnu.org/licenses/#LGPL> or the file `kpathsea/COPYING.LESSERv2`.

Appendix B References

1. Kpathsea: See *Kpathsea*.
2. Dvips and Afm2tfm: See *Dvips*.
3. The T_EX Users Group: <https://tug.org>. For an introduction to the T_EX system, see <https://tug.org/begin.html>.
4. TUGboat, the principal journal for the T_EX world: <https://tug.org/TUGboat>.
5. T_EX and computer typesetting in general:
<ftp://ftp.math.utah.edu/pub/tex/bib/texbook1.bib>.
6. For a bibliography of formal articles and technical reports on the T_EX project, see the books *T_EX: The Program* or *Metafont: The Program* cited below.
7. [Bil87] Neenie Billawala. Write-white printing engines and tuning fonts with Metafont. *TUGboat*, 8(1):29–32, April 1987. <https://tug.org/TUGboat/tb08-1/tb17billawala.pdf>.
8. [Hob89] John D. Hobby. A Metafont-like system with PS output. *TUGboat*, 10(4):505–512, December 1989. <https://tug.org/metapost>.
9. [Hob92] John D. Hobby. A User’s Manual for MetaPost. Technical Report CSTR-162, AT&T Bell Laboratories, 1992.
10. [Hob93] John D. Hobby. Drawing Graphs with MetaPost. Technical Report CSTR-164, AT&T Bell Laboratories, 1993.
11. [HS91] Samuel P. Harbison and Guy L. Steele Jr. *C—A Reference Manual*. Prentice-Hall, Upper Saddle River, NJ 07458, USA, third edition, 1991. An authoritative reference to the C programming language, and a good companion to Kernighan and Ritchie.
12. [KL93] Donald E. Knuth and Silvio Levy. *The CWEB System of Structured Documentation, Version 3.0*. Addison-Wesley, Reading, MA, USA, 1993. <https://ctan.org/pkg/cweb>.
13. [Knu84] Donald E. Knuth. A torture test for T_EX. Report No. STAN-CS-84-1027, Stanford University, Department of Computer Science, 1984.
14. [Knu86a] Donald E. Knuth. A Torture Test for METAFONT. Report No. STAN-CS-86-1095, Stanford University, Department of Computer Science, 1986.
15. [Knu86b] Donald E. Knuth. *The T_EXbook*, volume A of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
16. [Knu86c] Donald E. Knuth. *T_EX: The Program*, volume B of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
17. [Knu86d] Donald E. Knuth. *The METAFONTbook*, volume C of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
18. [Knu86e] Donald E. Knuth. *METAFONT: The Program*, volume D of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
19. [Knu86f] Donald E. Knuth. *Computer Modern Typefaces*, volume E of *Computers and Typesetting*. Addison-Wesley, Reading, MA, USA, 1986.
20. [Knu89] Donald E. Knuth. The errors of T_EX. *Software—Practice and Experience*, 19(7):607–681, July 1989. This is an updated version of Knuth:1988:ET.

21. [Knu90] Donald Knuth. Virtual Fonts: More Fun for Grand Wizards. *TUGboat*, 11(1):13–23, April 1990. <https://tug.org/TUGboat/tb11-1/tb27knut.pdf>.
22. [Knu92] Donald E. Knuth. *Literate Programming*. CSLI Lecture Notes Number 27. Stanford University Center for the Study of Language and Information, Stanford, CA, USA, 1992.
23. [Lam94] Leslie Lamport. *L^AT_EX: A Document Preparation System: User's Guide and Reference Manual*. Addison-Wesley, Reading, MA, USA, second edition, 1994. Reprinted with corrections, 1996.
24. [Lia83] Franklin Mark Liang. Word hy-phen-a-tion by com-put-er. Technical Report STAN-CS-83-977, Stanford University, August 1983. <https://tug.org/docs/liang/liang-thesis.pdf>.
25. [Mac91] Pierre A. MacKay. Looking at the pixels: Quality control for 300 dpi laser printer fonts, especially Metafonts. In Robert A. Morris and Jacques Andre, editors, *Raster Imaging and Digital Typography II—Papers from the second RIDT meeting, held in Boston, Oct. 14–16, 1991*, pages 205–215, New York, 1991. Cambridge University Press.

Index

- "
- " character, ignored in filenames 15
- #
- '#define' options 4
- \$
- \$ expansion in filenames 15
- %
- %& magic number 13
-
- starting a filename 7
- starts option names 7
- starts option names 7
- disable-dump-share configure option 13
- disable-mf-nowin 30
- enable-epsfwin 30
- enable-hp2627win 30
- enable-ipc configure option 18
- enable-mftalkwin 30
- enable-next 30
- enable-regiswin 30
- enable-suntoolswin 30
- enable-tektronixwin 30
- enable-unitermwin 30
- help common option 7
- verbose common option 7
- version common option 7
- with-editor=*cmd* 14
- with-mf-x-toolkit=*kit* 30
- with-x 30
- 8bit 9
- base=*base* 13
- base=*dumpname* 8
- change=*chfile* 32
- charcode-format=*type* 51, 53
- cnf-line 7
- D compiler options 4
- disable-write18 19
- dpi=*real* 43
- enable-write18 19
- enc 18
- file-line-error 8
- file-line-error-style 8
- fmt=*dumpname* 8
- fmt=*fmt* 13
- geometry, supported with Xt 30
- halt-on-error 8
- images 49
- ini 8, 12
- interaction=*string* 8
- ipc 18
- ipc-start 18
- jobname=*string* 8
- kpathsea-debug=*number* 8
- length=*number* 39
- loose 40
- lowercase 39
- magnification=*integer* 42, 43
- max-pages=*n* 42, 43
- mem=*dumpname* 8
- min-crossrefs=*n* 37
- mixedcase 39
- mktex=*filetype* 18, 28
- mltex 18
- mnemonics 49
- no-file-line-error 8
- no-mktex=*filetype* 18, 28
- no-parse-first-line 8
- no-shell-escape 19
- output-comment=*string* 19
- output-directory 8, 9
- output-level=*n* 43
- overflow-label-offset=*points* 31
- page-start=*page-spec* 42, 43
- parse-first-line 8
- progname=*string* 8, 13
- recorder 9
- shell-escape 19
- shell-restricted 19
- show-opcodes 43
- strict 40
- style=*mftfile* 33
- terse 37
- tex=*texprogram* 36
- translate-file=*tcxfile* 9
- troff 36
- T 36
- underline 39
- uppercase 39
- x 40

-
- ., used for output 9
- .2602gf 27
- .aux cross-reference files 37
- .base 28
- .bbl bibliography files 37
- .bib bibliography databases 37
- .blg BibT_EX log file 37
- .fmt 19
- .mf 27
- .mp 34
- .mps files and PDF 35
- .nnn PostScript figures 34
- .nngf generic fonts 27
- .tcx character translation files 9, 22
- .tex 17
- .tfm output 27, 34
- .Xdefaults 30
- .Xresources 30

- ^
- ^^ notation, avoiding 23

- \
- \bibliography 37
- \bibliographystyle 37
- \charsubdef and MLT_EX 21
- \countn 42, 43
- \font and dynamic generation 17
- \fontdimen 52
- \immediate\write18 24
- \input braced (grouped) filename 15
- \input filename caveats 15
- \input filenames 14
- \input quoted filename 15
- \input, and pipes 25
- \mag 42, 43
- \openin, and pipes 25
- \openout and security 17
- \openout, and pipes 25
- \output routine, and \write 24
- \pdfshellescape 25
- \string, and \input filenames 16
- \tracingcharsubdef and MLT_EX 22
- \tracinglostchars and MLT_EX 22
- \write18 shell escape extension 24

- ~
- ~ expansion in filenames 15

- 2**
- 2602gf 27

- 3**
- 32-bit architecture 13

- 6**
- 64-bit architecture 13

- 8**
- 8 bit clean 9
- 8 bit clean output, specifying 9
- 8-bit characters 22

- A**
- abbrv.bst 38
- accented character 22
- accents, hyphenating words with 21
- acknowledgements 1
- acm.bst 38
- Ada, WEB for 39
- additional Make targets 5
- afm2tfm 54
- AFM to TFM conversion 54
- afmtop1 54
- Aleph 26
- aliases for fonts 9
- alpha.bst 38
- American Mathematical Society, typesetting system 20
- AMST_EX 20
- apalike.bst 38
- architecture dependencies 13
- array limit, fixed 11
- array sizes 11
- assembly language routines 5
- autotrace 54
- Awk, WEB for 39

B

base file, determining 13
 base files 28
 base files, need mode definitions 29
 base files, plain only 29
 base files, sharing 13
bases Make target 5
 basic Bib \TeX style files 38
 basic fonts and macros 3
 batch languages 17
 BDF and GF conversion 54
beamer, package 21
beginfig 34
 Berry, Karl 1
 BIBINPUTS, search path for bib files 37
 bibliographies, creating 37
 bibliography 56
 bibliography items, cross-referenced 37
bibtex 37
 Bib \TeX 37
 Bib \TeX collection 37
 Bib \TeX style files 38
 BigEndian machines 13
 binaries, linking 8
 blank lines, in TCX files 23
 boxes, memory for 11
 braced filename for \backslash input 15
 breakpoints, memory for 11
 Breitenlohner, Peter 1
 BSTINPUTS, search path for bst files 37
btex for MetaPost labels 34
btxdoc.bib 37
btxdoc.tex 37
btzhak.tex 37
 byte position 48, 50
 byte swapping 13

C

c-sources Makefile target 5
 caveats for \backslash input filenames 15
 change files, and MFT 32
 change files, and Tangle 39
 change files, and Weave 40
 changing error messages style 8
 character codes, in GFtype output 50
 character codes, in PKtype output 48
 character codes, in TCX files 23
 character proofs of fonts 31
 character translation files 22
 CHARACTER property 52
 CHARDP property 52
 CHARHT property 52
 CHARIC property 52
 CHARWD property 52
chtopx 54
 class name for Metafont 30
cm.base 29

cmbase.mf 29
cmbase.mft 33
cmmf.base not recommended 29
 color, in DVItO μ P 36
 comments, in TCX files 23
 comments, MFT control 32
 common options 7
 commonalities 7
 compilation 3
 compile-time options 3, 4
 Computer Modern fonts, and Troff 35
 Computer Modern macros 29
Computer Modern Typefaces, production of 33
 configuration 3
 configuration file reading 9
 configuration file values 11
 configuration, compile-time 3
configure --with/--enable options 3
CONTENTS.tex 40
 Con \TeX t 20
 conventions for options, 7
 conversion, DVI to plain text 42
 conversion, GF to PK 47
 conversion, GF to plain text 49
 conversion, PK to GF 47
 conversion, PK to plain text 47
 conversion, property list to TFM 53
 conversion, property list to VF 54
 conversion, TFM to property list 51
 conversion, VF to VPL 53
 copyright notices 55
 Cork encoding and ISO input 23
 creating memory dumps 12
 cross-engine functionality 25
 cross-referenced bibliography items 37
 cross-references, omitting 40
 current directory, used for output 9
 Curtis, Pavel 1
 Cweb 39
 CWEB 39

D

date and time, in memory dumps 13
 debugging DVI utilities 43
 debugging flags, specifying 8
 decimal character codes, in TCX files 23
 dependencies, hardware 13
 design-size units 52
 device definitions, for Metafont 29
 device-independent width 48, 50
 directory structure 3
DISPLAY 30
 dot files, written by \TeX programs 17
 double quote character, ignored in filenames 15
 downloading of fonts for MetaPost labels 35
DrawingServant 30
 dump file 8

dumping memory 12
 DVI comment, specifying 19
 DVI files, converting to MPX 36
 DVI files, explained 46
 DVI format definition 42
 DVI opcodes, showing 43
 DVI utilities 42
dvicopy 42
dvitomp 36
dvitype DVI validation 42
dvitype output example 43
dvitype.web 42
 dx horizontal escapement 48, 50
 dy vertical escapement 50
 dynamic array allocation 11
 dynamic Metafont mode
 definitions with **smode** 29
 dynamic packing variable 48

E

e response at error prompt 14
 e-circumflex 22
e-TeX 26
e.mft 33
 EC fonts 17, 27
 editing of bitmap fonts 54
 editor invoked at error 14
 eight-bit characters in filenames 15
empty.tcx 23
 endian dependencies 13
eoc GF command 50
 Explain 21
epsf 30
epTeX 26
 errors, editor invoked at 14
 escapement, horizontal 48, 50
 escapement, vertical 50
etex for MetaPost labels 34
etex is pdfTeX 26
eupTeX 26
 executables, shared initial and virgin 12
 exit status, of shell escape 25
expand_depth 11
 expanded plain format 21
 expansion limit, recursive 11
 expansion, and **\input** filenames 15
 extensions to TeX 25
extra_mem_bot 11

F

FACE property 52
FAMILY property 52
 Ferguson, Michael 21
 file formats for fonts 46
 file recorder 9
 filename conventions, in input files 14
 filenames starting with ‘_’ 7
 first line of the main input file 9
 fixed-point arithmetic 5
FIXPT 5
 flag byte 48
 floating-point arithmetic 5
 floating-point values 13
fmt file, determining 13
fmt files 19
fmt files, sharing 13
fmts Make target 5
 font aliases 9
 font character code, translating 24
 font design 27
 font downloading for MetaPost labels 35
 font file formats 46
 font proofs 31
 font utilities 46
 font utilities, non-Web2c 54
fontforge 54
fontinst, for creating virtual fonts 54
 fonts, basic 3
 format files 20
 formats for TeX 20
formats Make target 5
 fraction routines 5
 Free Software Foundation
 documentation system 20
 freedom of Web2c 1
ftp.math.utah.edu 37

G

generating source specials 19
 geometric designs 27
 geometric font scaling 46
 geometry for Metafont 30
getopt_long_only 7
 GF files, explained 46
 GF files, output by Metafont 27
 GF format definition 46
 GF output 27
 GF, converting PK to 47
 GF, converting to PK 47
gftodvi 31
gftopk 47
gftopxl 54
gftype GF validation 49
gftype.web 46
 glue ratio representations 13
 glue, memory for 11

glyph substitutions 21
 gray font 31
 group-delimited filename for `\input` 15
 Gruff, Billy Goat 5
`gsftopk` 54

H

Harbison, Samuel P. 13
 hardware and memory dumps 13
`headerbyte` information 52
 height, in pixels 48
 help, online 7
 Herberts, Mathias 30
 hex character codes, in TCX files 23
 HINT (Hint Is Not `TEX`) 26
 history 1
`hiTEX` 26
 Hobby, John 1
 horizontal escapement 48, 50
`hp2627` 30
 human languages, supported in `TEX` 21
 human-readable text, converting DVI to 42
 human-readable text, converting GF to 49
 human-readable text, converting PK to 47
 human-readable text, converting TFM to 51
 human-readable text, converting VF to 53
 hypertext 26
 hyphenation and languages 21
 hyphenation patterns, creating 24

I

ice cream 1
 identifier case 39
 identifier collisions 40
 identifier length 39
 identifiers with underlines 39
`ieeetr.bst` 38
`il1-t1.tcx` 23
`il2-t1.tcx` 23
 Info format 20
 initial form, enabling 8
 initial Metafont 28
 initial MetaPost 36
 initial programs 12
 initial `TEX` 19
 initializations, lengthy 12
 input filenames 14
`install-bases` Make target 5
`install-fmts` Make target 5
`install-formats` Make target 5
`install-mems` Make target 5
 installation 3
 interaction between TCX files and ‘`-8bit`’ 24
 interaction mode 8
 international characters 22
 introduction 1

IPC 25
`IPC_DEBUG` 5, 25

J

job name 8

K

kernel table, in TFM files 52
 keyboard character code, translating 24
 Knuth, Donald E. 1, 32
`KPATHSEA_DEBUG` 8
`KRN` property 52

L

label font 31
`LABEL` property 52
 language support in `TEX` 21
 languages, hyphenation rules for 24
`LATEX` 20
 Latin Modern 54
 left side bearing 48, 50
 legalisms 55
`libsigsegv` library 11
 licensing terms 1
`LIG` property 52
 ligature table, in TFM files 52
`LIGTABLE` property 52
 linking binaries 8
 links to binaries 13
 literate programming 39
 LittleEndian machines 13
 location of `texmf.cnf` in `TEX Live` 11
 log file, `BibTEX` 37
`long` data type, size of 13
 Lua 26
`LuaTEX` 26

M

machine dependencies 13
 machine-readable, converting
 property lists to 53, 54
 MacKay, Pierre 47
 macro packages, major `TEX` 20
 macros, basic 3
 macros, redefining in memory dumps 12
 magnification 42, 43
`main_memory` 11
 Make targets, additional 5
 Martin, Rick 1
 Mathematical Reviews 20
 mathematical typesetting 17
 mem file, determining 13
 mem files, sharing 13
 memory dump to use, determining 13

- memory dumps 12
 - memory dumps and hardware 13
 - memory dumps, contain date and time 13
 - memory dumps, creating 12
 - `mems` Make target 5
 - meta characters in filenames 15
 - Metafont 27
 - Metafont geometry 30
 - Metafont graphics 30
 - Metafont input files 27
 - Metafont invocation 27
 - Metafont meets PostScript 34
 - Metafont online support, new devices 30
 - Metafont source, prettyprinting 32
 - Metafont, compatibility in MetaPost 36
 - Metafont, initial 28
 - Metafont, MetaPost, and \TeX 11
 - MetaPost 34
 - MetaPost and plain Metafont compatibility 36
 - MetaPost input files 34
 - MetaPost invocation 34
 - MetaPost source, prettyprinting 33
 - MetaPost, initial 36
 - MetaPost, \TeX , and Metafont 11
 - `metatype1` 54
 - `mf` 27
 - `mf.base` 28
 - MFEDIT 14
 - `mfplain` 36
 - `mfput` 27
 - `mft` 32
 - `mftalk` 30
 - MFTERM 30
 - `mftmac.tex` 32
 - micro-typography 26
 - `mktexmf`, disabling 27
 - `mktextfm`, disabling 17
 - `mltex` 21
 - ML \TeX , enabling 18
 - mode needed to run Metafont 27
 - `mode_def` 29
 - `mode_setup` 29
 - modes file needed for Metafont 29
 - `modes.mf` recommended modes file 29
 - modifying `texmf.cnf` in \TeX Live 11
 - Morgan, Tim 1
 - Morris, Bob 1
 - MPEDIT 14
 - `mpgraph.pdf` 34
 - `mpman.pdf` 34
 - `mpost` 34
 - `mpost`, reason for name change 3
 - `mpout` 34
 - `mproof.tex` 35
 - `mptrap` Make target 5
 - `mptrap` test 5
 - `mptrap.readme` 5
 - MPX files, converting from DVI files 36
 - Multi-lingual \TeX 21
 - multiple spaces, and `\input` filenames 15
- ## N
- N tilde 22
 - new graphics support for Metafont 30
 - `newrow` GF command 50
 - `next` 30
 - `NO_X11WIN` 30
 - non-Unix system, compiling on 5
 - non-windows-capable Metafont 30
 - NUL, not allowed in filenames 15
- ## O
- octal character codes, in TCX files 23
 - offset for overflow labels 31
 - Omega 26
 - online Metafont graphics 30
 - opcodes, showing DVI 43
 - OpenType support 26
 - optical font scaling 46
 - option conventions 7
 - origin 48
 - output directory, specifying 8, 9
 - output file location 9
 - output files, written by \TeX programs 17
 - `output_comment` for DVI files 19
 - overflow label offset 31
 - overflow, of runtime stack 11
- ## P
- packet length 48
 - page, starting 42, 43
 - parsing the first line 8
 - Pascal, creating from WEB 39
 - `patgen` 24
 - path searching 9
 - path searching debugging 8
 - `pdf \TeX` 26
 - PDF 26
 - PDF, and `.mps` files 35
 - permissions, legal 55
 - PFA and PFB conversion 54
 - `pfaedit` 54
 - PiCT \TeX , increasing memory for 11
 - pipes, reading and writing 25
 - pixel height 48
 - pixel width 48
 - PK bitmaps from PostScript 54
 - PK files, explained 46
 - PK files, not output by Metafont 27
 - PK format definition 46
 - PK, converting GF to 47
 - PK, converting to GF 47
 - `pktogf` 47

pktype PK validation 47
pktype.web 46
 PL files, explained 46
 plain Metafont, compatibility in MetaPost 36
 plain text, converting DVI to 42
 plain text, converting GF to 49
 plain text, converting PK to 47
 plain text, converting TFM to 51
 plain text, converting VF to 53
plain.base 28
plain.bst 38
plain.fmt 20
plain.mft 33
pltotf 53
 pool file, writing 39
 Poole, Simon 30
pooltype 40
 portable filenames 15
 PostScript fonts, and Troff 35
 PostScript meets Metafont 34
 PostScript output 34
 PostScript to PK bitmaps 54
 PostScript Type 1 font conversion 54
 PostScript, and font scaling 46
potrace 54
 predefined macros and memory dumps 12
 prettyprinting Metafont source 32
 prettyprinting WEB programs 40
 primitives, new 26
 printable characters, specifying 23
 printer characteristics, for Metafont 29
 production use 12
 program name, determines memory dump 13
 program names, special 8, 18
prologues 36
 prologues, and EPSF output 35
proof mode 27
 proof sheets, of fonts 31
 property list format 51
 property list, converting TFM to 51
 property list, converting VF to virtual 53
ps2pk 54
psfonts.map, read by MetaPost 35
pTeX 26
 PXL files, explained 46
pxtoch 54

Q

quoted filename for `\input` 15

R

Raichle, Bernd 21
 reading, additional 1
 readonly directory, running T_EX in 9
 reallocation of arrays 11
 recursive expansion limit 11
 redefined character substitutions 22
 reference pixel 48
 references 56
regis 30
 Regis graphics support 30
 regression testing 19
 repeated rows 49
 representation of strings 41
 restricted shell escapes 24
 right side bearing 48, 50
 Rokicki, Tomas 1
 run length encoded bitmaps 49, 50
 runtime options 11
 runtime stack overflow 11

S

scaled pixels 48, 50
 scaling of fonts 46
 security, and `\openout` 17
 security, and output files 17
 security, and shell escapes 24
 security, and `write` 35
 segmentation fault 11
 shapes 27
 sharing memory dumps 13
 shell commands in T_EX 24
shell_escape enabling in T_EX 24
shell_escape_commands 25
siam.bst 38
 side bearings 48, 50
SIGSEGV 11
 slant font 31
 slides, producing 21
 SliT_EX 21
 small Metafont memory and modes 29
smode and dynamic Metafont mode definition .. 29
 sockets 25
 space-terminated filenames 14
 Spiderweb 39
 Stallman, Richard 1
 starting page 42, 43
 Steele Jr., Guy L. 13
 stopping at the first error 8
 strategy, overall 1
 string numbers, displaying 40
 string pool, writing 39
 string representation 41
 style design, for BibT_EX 37
 style files 33
 substitutions of font glyphs 21
sun 30

sun-gfx.c 30
 Suntools 30
 SunView 30
 swap space, as array limit 11
 swapping bytes 13
 syntax of TCX files 23
system C library function 24
 system command 24
 system fonts, using 26

T

T1 encoding and ISO input 23
 tabs, and `\input` filenames 15
 Tachikawa, Elizabeth 47
tangle 39
 targets, additional Make 5
 TCX character translation files 22
 technical illustrations, creating 34
tek 30
 Tektronix 30
 Tektronix 4014 30
 terminator for filenames 14
TERM 30
 terse output 37
 te \TeX distribution 1
tex 17
tex.fmt 20
 \TeX , bibliographies for 37
 \TeX , creating from Metafont 32
 \TeX , creating from WEB 40
 \TeX , description of 17
 \TeX , extensions to 25
 \TeX , format packages for 20
 \TeX , initial 19
 \TeX , input files found 17
 \TeX , invocation 17
 \TeX , Metafont, and MetaPost 11
 \TeX , Web2c implementation of 1
 TEXTBIB, search path for bib files 37
 TEXEDIT 14
texfonts.map 9
 Texinfo 20
texmf.cnf 9, 11
texmf.cnf for editors 14
texmf.cnf for shell escapes 24
texmf_casefold_search 11
texmfmp.c 30
 TEXMFOUTPUT, used for reading 10
 TEXMFOUTPUT, used if ‘.’ unwritable 9
texput 17
 TFM files, converting property lists to 53
 TFM files, explained 46
 TFM files, output by Metafont 27
 TFM files, output by MetaPost 34
 TFM width of characters 48, 50
tftopl 51
 three programs 11

time and date, in memory dumps 13
 title font 31
tl-check-fmtshare 13
 tokenization, and `\input` filenames 15
 toolkits, X 30
 torture tests 5
 translation file for \TeX , specifying 9
 translation from WEB to C 1
trap Make target 5
 trap test 5
trapman.tex 5
 Trickey, Howard 1
trip Make target 5
 trip test 5
tripman.tex 5
triptrap Make target 5
 Troff, and MetaPost 35
troff, supported in MetaPost 34
 Troff, WEB for 39
 Trojan horses and \TeX programs 17
 TrueType support 26
 TUGboat bibliography 37
 Type 1 conversion 54
 type design, personal 29
 type programs, DVI 42
 type programs, GF 49
 type programs, PK 47
 type programs, pool 40
 typeface families 27
 typesetting 17

U

Unicode 26
 Unicode input 18
 Unicode input, native 26
uniterm 30
unsrt.bst 38
 up \TeX 26
 UTF-8 input 18
 UTF-8 input, native 26

V

validation, of DVI files 42
 validation, of GF files 49
 validation, of PK files 47
 validation, of TFM files 51
 validation, of VF files 53
 verbose Bib \TeX output, suppressing 37
 verbosity, enabling 7
 version number, finding 7
 vertical escapement 50
 VF files, converting property lists to 54
vftovp 53
 virgin programs 12
 virtual font creation 54
 virtual fonts, expanding 42

virtual-fonts.knuth..... 46
 virtualfonts.txt 46
 vptovf..... 54

W

weave..... 40
 web environments, and security 25
 WEB pool files, displaying 40
 WEB programs, compiling 39
 WEB programs, typesetting 40
 WEB2C, search path for TCX files 23
 Weber, Olaf..... 1
 webmac.tex..... 40
 webman.tex..... 39
 WEB 39
 whitespace, in TCX files 23
 whitespace-terminated filenames 14
 width, device-independent 48, 50
 width, in pixels 48
 word processor, not 17
 writing memory dumps 12

X

x offset 48
 X bitmap fonts 54
 X class name for Metafont 30
 X resources 30
 X toolkits and Metafont 30
 xampl.bib 37
 xbfed, bitmap font editor 54
 Xe_TE_X..... 26
 xfed, bitmap font editor 54
 xfedor, bitmap font editor 54
 Xlib 30
 Xlib support 30
 Xt 30
 Xt support 30
 xterm 30

Y

y offset 48